

Right Strap




For 1/2", 3/4" and NOW 1" CTS

**The Right Strap for
 Mounting Versatility for
 All CTS Tubing**

1. When installed in Half Clamp fashion, RightStrap provides a "silence gap" between tubing and framing . . . thus reducing the noise generated when water supply tubing expands and rubs against wood with other half clamps.
2. Reversing the Removable Barbed Nail allows RightStrap to be mounted at predesignated positions so tubing may be "popped-in" afterward.
3. RightStrap's perpendicular nail channel allows "cradle mounting" capability like a Mini J-Hook installation. Tubing may be "popped-in" afterward, also.

Installs 3 Ways

Silence
 Gap



- Use it like a Half Clamp, Full Clamp or Mini J-Hook
- Factory Assembled for Half Clamp Installation
- For All Metal and Plastic 1/2", 3/4" and NOW 1" Copper Tube Size Materials
- Allows for Expansion and Contraction of Supply Tubing
- Greatly Reduces the Chances for Noise Common to Overly Restrictive Support Systems

**No Pinning, No Binding,
 NO COMPLAINTS!**

*PATENT PENDING

CAUTION! SOME CPVC TUBING MANUFACTURERS ADVISE AGAINST USING "SINGLE NAIL TALON TYPE STRAPS" THAT TEND TO OVERLY RESTRICT MOTION FOR THERMAL EXPANSION, CITING SUCH USE AS UNACCEPTABLE . . . HOWEVER, RIGHTSTRAP DOES NOT PIN TUBING TO STUD NOR RESTRICT ITS MOTION.

| Product Description | Product Code | Bag Qty. | Clamp Size | Units/Case | Lbs./Case |
|--|--------------|----------|------------|------------|-----------|
| RightStrap Multi-Functional Pipe Clamp - | | | | | |
| Plastic clamp preloaded with removable barbed nail. | | | | | |
| Supports copper, PEX, polybutylene and ideally isolates CPVC tubing from wood framing. | | | | | |
| Supports 1/2" Tubing | 82852 | 50 | 1/2" | 2000 | 22 |
| Supports 3/4" Tubing | 82854 | 50 | 3/4" | 1000 | 14 |
| Supports 1" Tubing | 82856 | 50 | 1" | 500 | 13 |