

Water Hammer Arresters

➤ Sizing Guideline

The following should be used as a guide only. Always consult local plumbing codes for specific requirements before installation.

RESIDENTIAL



Hotels



Motels



Multi-Family Dwellings



Single-Family Dwellings

Single-Fixture & Private Plumbing Groups

Applications: Not just for homes. Plumbing fixtures in homes, duplexes, apartments, condominiums, motels, hotels and military housing.

Sizing/Placement Guideline: Point-of-use AA size arrester on both hot and cold lines. Place on ice makers, dishwashers, washing machines and tub/shower valves.



Tub/Shower



Ice Maker



Dishwasher



Laundry



MIP



Laundry

Arrester Group: Any ASSE 1010 Certified AA size arrester. Various connection size and type are for the installer's convenience.

COMMERCIAL



Office Buildings



Hospitals



Correctional Institutions




Retail Buildings

Multi-fixture Plumbing Groups

Applications: Plumbing fixtures in office buildings, retail, schools, hospitals, correctional facilities and public buildings.

Sizing/Placement Guideline: The properly sized arrester corresponds to the total number of fixture units on each hot and cold branch line. Place each arrester at end of the branch line.



Arrester Group: Any ASSE 1010 Certified A, B, C, D, E, or F size arrester. Various connection size and type are for the installer's convenience.



INDUSTRIAL



Industrial Fluid Handling



Commercial Laundries



Up-Feed Pump Systems

Large Industrial Piping Systems

Applications: Industrial equipment, food processing, commercial laundry, up-feed pump systems, irrigation and waste treatment systems.

Sizing/Placement Guideline: To size an arrester for industrial applications, use the Industrial Equation, custom sizing the arrester given the system information of a particular project. A computer spreadsheet version of this equation is also available.



Arrester Group: Large industrial size arresters, 200-400 cubic inch size.



2 Available for Large Top only | 3 Available for round nickel-bronze strainers only | 4 For 3" and 4" drains - In place of standard gasket | 5 Extends head 2" (min) to 4" (max) above Coring Sleeve