



UTILITY ENTERPRISES, INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

AQUA-PLUG LEAK STOPPING CEMENT

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call **INFOTRAC** - Day or Night: **1-800-535-5053**
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) **IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name: Cleaning Compounds, NOI
Chemical Family: Carbonates
DOT Hazard Class: N/R

CAS NO.: Mixture
UN/NA#: N/R
DATE OF ISSUE: 4/11

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS #	TLV/PEL	AGENCY	TYPE	SARA-313(% Range)
Hydrated Lime	1305-62-0	N/A			
Portland Cement	65997-15-1	10 mg/m ³ (total dust)			
Silica	7631-86-9	0.10 mg/m ³			

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Move person away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek medical attention. For direct contact hold eyelids apart for at least 15 minutes

SKIN CONTACT: Remove contaminated shoes and clothing and cleanse affected areas thoroughly by washing with mild soap and water. If irritation persists **seek medical attention.**

INHALATION: (breathing) Move person away from exposure into fresh air. If symptoms persist, seek medical attention.

INGESTION: (swallowing) If swallowed, seek emergency medical attention. Do not induce vomiting. .

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: May cause burning and irritation upon contact.

SKIN CONTACT: Direct Skin contact may cause irritation or dermatitis.

INHALATION: (breathing) Prolonged inhalation of dust may result in irritation of the throat and lungs.

INGESTION: (swallowing) Ingestion of this product may cause the following: Irritation of throat and digestive tract, signs of nervous system depression, such as headache, drowsiness, dizziness, loss of coordination, fatigue, and nausea.

SECTION IV - SPECIAL PROTECTION INFORMATION

NOTE: Sanding or grinding the dry surface of this material may result in the introduction of dust particles which require the following precautions:

VENTILATION: Use adequate ventilation to maintain airborne concentrations within established safe exposure limits.

RESPIRATORY PROTECTION: The use of respiratory protection is advised when concentrations exceed the established safe exposure limits.

PROTECTIVE GLOVES: The use of gloves is advised to prevent irritation.

EYE PROTECTION: Approved eye protection to safeguard against potential eye contact, irritation or injury is highly recommended.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Avoid open flame and strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: carbon dioxide, carbon monoxide, soot smoke, vinyl/acrylic monomers.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL: Follow normal cleanup procedures. Collect large spills with shovel or pump to other leak proof container. Spread sand over spill area. Clean with detergent solution.

WASTE DISPOSAL METHOD: Dispose of product in accordance with local, county, state, and federal regulations.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Do not get in eyes, skin or clothing. Keep containers tightly closed, cool, dry, and away from all sources of ignition. **KEEP FROM FREEZING**



UTILITY ENTERPRISES, INC.
 700 MAIN STREET, WESTBURY, NY 11590
 (516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

AQUA-PLUG LEAK STOPPING CEMENT

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Product is non-combustible
FIRE AND EXPLOSION HAZARD: None
FIRE FIGHTING PROCEDURES: No special procedures required. Product is non-combustible.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F): N/A	PERCENT VOLATILE: NONE
SPECIFIC GRAVITY (68 F): >1	FLASH POINT (TCC, DEG F): n/a
RELATIVE EVAPORATION RATE (ESTIMATED): <1	PERCENT SOLUBILITY IN WATER: 100%
VAPOR PRESSURE @20C mmHg (CALCULATED): <1	

SECTION X - OTHER REGULATORY DATA

<u>SARA</u>	<u>HMIS</u>		
<i>SECTION 302:</i> NONE	Health:		1
<i>SECTION 311 & 312:</i> NONE	Flammability:		0
<i>SECTION 313:</i> See Section I.I	Reactivity:		0

TSCA
 All components are in full compliance with the TSCA inventory.

CALIFORNIA PROPOSITION 65
 NOT LISTED

RCRA
 NOT REGULATED

CERCLA
 NOT REGULATED

CARCINOGENICITY:
 NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufactures and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.