

Red Gage Fluid

Safety Data Sheet

Issue date: 03/21/2005 Revision date: 12/13/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name. : Red Gage Fluid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Gage Fluid

1.3. Details of the supplier of the safety data sheet

Dwyer Instruments
102 Highway 212
Michigan City, IN 46361
T 219-879-8868 - F 219-872-9057

1.4. Emergency telephone number

Emergency number : Call CHEMTREC day or night. Domestic North America call- 800-424-9300; International call - 703-527-3887 (collect accepted) CCN206315

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4 H227
Carc. 1B H350
Asp. Tox. 1 H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H350 - May cause cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P308+P313 - IF exposed or concerned: Get medical advice/attention
P331 - If swallowed, do NOT induce vomiting
P370+P378 - In case of fire: Use ... for extinction
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to ...

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	Note	%	GHS-US classification
Petroleum distillates, hydrotreated light	(CAS No.) 64742-47-8	2 1	40-70	Not classified
Distillates, petroleum, hydrotreated light naphthenic	(CAS No.) 64742-53-6	3	40-70	Not classified
C.I. Solvent Red 164	(CAS No.) 71819-51-7	1 >3	0.1-1.0	Not classified

(1) Toxicity data is not available for this component.

(2) This component is hazardous as defined in OSHA Hazard Communications (29 CFR 1910.1200). Combustible.

(3) Based on the data available to Dwyer Instruments, Inc., these components in this product are not hazardous under OSHA hazard communications (29 CFR 1910.1200).

Red Gage Fluid

Safety Data Sheet

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration.
- First-aid measures after skin contact : For skin contact, flush with large amounts of water. If irritation persists, get medical attention.
- First-aid measures after eye contact : Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
- First-aid measures after ingestion : If the material is swallowed, get immediate medical attention or advice. Do not induce vomiting unless directed to do so by medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation.
- Symptoms/injuries after eye contact : May cause eye irritation.
- Symptoms/injuries after ingestion : Not considered a likely route of exposure under normal product use conditions. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use foam, dry chemical or water spray to extinguish fire.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : None known.
- Explosion hazard : None known.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with the skin and the eyes. Wear appropriate protective clothing and respiratory protection for the situation.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop the flow of material, if this is without risk.
- Methods for cleaning up : Absorb spill with inert material. Shovel or sweep up and put in a closed container for disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep the container tightly closed and in a cool, well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No exposure limits have been established for any of this product's components.

Red Gage Fluid

Safety Data Sheet

8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits (where available).
Hand protection	: Use impervious gloves such as neoprene, nitrile, or rubber for hand protection.
Eye protection	: Wear safety glasses; chemical goggles (if splashing is possible).
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Red
Odor	: Characteristic
Odor threshold	: No data available
pH	: 5.78
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 72.2 °C (162 °F)
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity	: 0.826
Solubility	: Insoluble.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Avoid heat, open flames and ignition sources.

10.5. Incompatible materials

Oxidizing materials.

10.6. Hazardous decomposition products

Decomposes to form toxic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Red Gage Fluid

Safety Data Sheet

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.2 mg/l (Exposure time: 4 h)

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	2.18 mg/l (Exposure time: 4 h)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 fishes 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	4720 mg/l (Exposure time: 96 h - Species: Den-dronereides heteropoda)
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LC50 fishes 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. UN number

DOT NA no. NA1993

14.2. UN proper shipping name

DOT Proper Shipping Name : Combustible liquid, n.o.s. (Petroleum distillates, hydrotreated light)
Department of Transportation (DOT) Hazard Classes : COMB LIQ – Combustible liquid 49 CFR 172.101 (d)(4)
DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada
G - Identifies PSN requiring a technical name
Packing group (DOT) : III - Minor Danger

Red Gage Fluid

Safety Data Sheet

DOT Special Provisions (49 CFR 172.102)	:	IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, and Tf is the temperature in degrees Celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	150
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
International Air Transport Association (IATA)	:	Not classified as hazardous by IATA DGR.

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

IATA Quantity Limitations Passenger and Cargo aircraft : Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

15.3. US State regulations

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

U.S. - Massachusetts - Right To Know List

California Proposition 65

Contains no substances known to the State of California to cause cancer or reproductive harm.

Red Gage Fluid

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Flam. Liq. 4	Flammable liquids Category 4
H304	May be fatal if swallowed and enters airways
H350	May cause cancer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.