Material Safety Data Sheet

MSDS No. 0081 Rev. 8

0816/0826/0810/0820 Series Spec Compliant Silicone Sealant – Acetoxy Cure - Clear, White & Colors

Emergency Phone No. 800-53<u>5-5053 - INFOTRAC</u>

	SECTION 1 – P	RODUCT NAME &	MANUFACTURER I	NFORM	ATION		
PRODUCT NAME	Silicone Sealant – O	Clear & All Colors					
MANUFACTURER'S N. TELEPHONE NUMBER		918-825-5744					
STREET ADDRESS	4175 Webb Street	4175 Webb Street					
CITY / STATE / ZIP	Pryor, Oklahoma 74	4361					
SECTION 2 – COMPOSITION / HAZARDOUS INGREDIENTS					TLV	PEL	UNITS
PRODUCT CONSISTS	OF:						
Ethyltriacetoxy	rsilane (17689-77-9)	< 6%	NE	NE			
Methyltriacetor	xysilane ** (4253-34-3)		< 6%	10	10	ppm	
Titanium Diox	ide *** (13463-67-7) (In white	< 5%	10	15	mg/m3		
Silica, amorphe	< 13	20	20	mg/m3			
Hydroxy-termi	> 50	10	10	ppm			
Polydimethylsi		< 10	10	10	ppm		
Non-hazardous	> 10	NA	NA				
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Observe limits for acetic acid formed during curing on exposure to water or humid air. ***Inhalation of particulates unlikely due to product's physical state.							
Calculated VO							
SECTION 3 – HAZARDS IDENTIFICATION							
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	🛛 Inhala	Inhalation Ingestion				
EMERGENCY OVERVIEW	Clear/opaque or colored paste tract irritation.	e. Harmful if swallowed or absorbe	d through skin. May cause eye & s	kin irritation. N	lay cause nos	e, throat & re	espiratory
EFFECTS OF OVEREXPOSURE	<u>Acute</u> : (Eye) – Direct contact may cause moderate irritation. (Skin) – May cause moderate irritation. (Inhalation) – Slight irritation to respiratory passages. (Oral) – No significant effects expected from a single short-term exposure. <u>Prolonged/Repeated Exposure</u> : No known applicable information.						
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.						
		SECTION 4 – FIRS	ST AID MEASURES				
SKIN CONTACT	Wash w/ soap &	water for @ least 15 minutes. Get	medical attention if symptoms per	sist. Remove &	wash contam	inated clothi	ng.
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.						
INHALATION	No first aid should be needed under normal use. Remove to fresh air if needed.						
INGESTION Not intended for ingestion. No first aid should be needed. Get medical attention if irritation persists. Treat according to person's condition & specifics of exposure.							

SECTION 5 – FIRE FIGHTING MEASURES							
FLAMMABLE	Yes 🛛	No No					
EXTINGUISHING	Carb	on Dioxi	de, Dry Chemical	, Foam, Water Spray			
MEDIA FLASHPOINT (°F) &	&	> 212 (Cl	osed Cup)		UPPER EXPLO		NE
METHOD LOWER EXPLOSIV	E LIMIT	NE			(% BY VOLUM AUTOIGNITIO	N	NE
(% BY VOLUME) UNUSUAL FIRE & I	EXPLOSION	None			TEMPERTURE	(°F)	
HAZARDS SPECIAL Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces. Thermal breakdown of this product during fire or high heat conditions may evolve the following hazardous decomposition products: Silicon dioxide. Carbon oxides & traces of incompletely burned carbon compounds. Formaldehyde.							
	_		SECTIO	N 6 – ACCIDE	NTAL RELE	ASE MI	EASURES
PROCEDURES	Wea	r proper p	rotective equipm	ent (Section 8). Use abso	rbent material or scra	pe up dried 1	material & place in approved container.
			SE	CCTION 7 – HA	NDLING &	STORA	GE
HANDLING PROCEDURES & Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use w/ adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use appropriate respirator. Avoid eye contact. Avoid skin contact.							
STORAGE REQUIREMENTS Keep container closed & store away from water or moisture. Avoid extreme heat or cold. Store away from oxidizing materials. When heated to temperatures above 300F in presence of air, product may form formaldehyde vapors.							
		SECT	ION 8 – EX	XPOSURE CO	NTROL / PE	RSONA	L PROTECTION
RESPIRATORY	RESPIRATORY No respiratory protection should be needed. As Engineering Controls, Local & General Ventilation is recommended. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm & ACGIG TLV: TWA 10 ppm, STEL 15 ppm. Use respiratory protection if adequate local exhaust ventilation unavailable. OSHA respirator regulations 29 CFR 1910.134 should be followed, using NIOSH/MSHA approved respirators. <u>Spills</u> : Full face respirator.						
EYEWEAR							
CLOTHING / GLOVES	Nitrile rubbe	er or buty	l rubber gloves. A	void skin contact.			
HYGENIC PRACTICES	Remove & v	Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.					
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES							
PHYSICAL STATE			Viscous pa	iste	ODOR & APPEARANCE	Clear or	r colored paste w/ acetic acid odor
SPECIFIC GRAVIT	Y		Approximately 1	.0 to 1.1	VAPOR DENSITY (AIR=1)	NE	
EVAPORATION RA	ATE		NE		BOILING RANGE (°I	F) NE	
рН			NE		SOLUBILITY IN WATER	NE	
VAPOR PRESSURE Hg)	E (MM		NE		%/WT VOLATILE (TNV)	NE	
SECTION 10 – STABILITY AND REACTIVITY							
STABILITY Xes No Stable under normal conditions.							
INCOMPATABILIT	INCOMPATABILITY Xes No Materials to Avoid: Water, moisture or humid air can cause hazardous vapors to form (Sec. 8). Oxidizing material can cause a reaction.						
CONDITIONS TO AVOID	None.						
HAZARDOUS POLYMERIZATION	HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.						

SECTION 11 – TOXICOLOGICAL INFORMATION / CARCINOGENICITY ACGIH No known applicable information. This product does not contain carcinogens (@0.1% or greater) as defined by IARC, NTP or OSHA. OSHA No known applicable information. See above. IARC No known applicable information. See above. NTP No known applicable information. See above. DATA WITH POSSIBLE RELEVANCE TO HUMA No known applicable information. See above. NCE TO HUMANS SECTION 12 – ECOLOGICAL INFORMATION AQUATIC TOXICITY Complete information is not yet available. Ecotoxicity Classification Criteria: Hazard Parameters (LC50 or EC50) High Medium Low Acute Aquatic Toxicity mg/L <= 1 >1 & <= 100 >100 Acute Terrestrial Toxicity <= 100 >100 & <=2000 >2000 (Table adapted from "Environmental Toxicology & Risk Assessment", ASTM STP 1179, p. 34, 1993) (Table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material. SECTION 13 – DISPOSAL CONSIDERATIONS WASTE DISPOSAL Dispose of material in accordance w/ Federal, State & Local regulations. FPA WASTE CODE IF None. RCRA Hazard Class (40 CFR 261): Not classified as a hazardous waste. State or local laws may impose additional regulatory requirements DISCARDED (40CFR Sec.261) regarding disposal. SECTION 14 – TRANSPORT INFORMATION SPECIAL SHIPPING DOT Road Shipment Information (49 CFR 172.101): Not subject to DOT. Ocean Shipment (IMDG): Not subject to IMDG code. Air Shipment INFORMATION (IATA): Not subject to IATA regulations. SECTION 15 – REGULATORY INFORMATION CERCLA – SARA Section 304 CERCLA: None. Section 302 (Extremely U.S. See Section 16. STATE HAZARD CATEGORY Hazardous Substances): None. Section 312 (Hazard Class): REGS Acute: Yes. Chronic: No. Fire: No. Pressure: No. Reactive: No. **SARA 313** None present or none present in regulated quantities. TSCA All ingredients either on TSCA Inventory or exempt. SECTION 16 - OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND Prop 65 Ingredients: (Known to State of California to cause cancer) None. NJ Right-to-Know: (Top 5 Ingredients): Hydroxy-terminated Dimethyl Siloxane (70131-67-8), Silica, amorphous (7631-86-9), Methyltriacetoxysilane (4253-34-3), Ethyltriacetoxysilane (17689-77-9), Polydimethylsiloxane (63148-62-9). Pennsylvania Right-to-Know (Non-Haz @ >3%): Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ingredients Known to State of California to cause birth defects or reproductive harm: None. NFPA Profile: Health: 2, Flammability: 1, Reactivity: 0. HMIS Profile: Health: 1, Flammability: 0, Reactivity: 0, PPE: B. Note: Silicone sealant colors, other than white, may contain a small amount of Carbon Black (1333-86-4). INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 - INFOTRAC

LEGEND: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act, NFPA – National Fire Protection Association.

Reviewed By: <u>Larry G. Brandon</u>	VP Technology & General Manager	January 27, 2014
NAME	TITLE	DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.