



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

SAFETY DATA SHEET

Leak Sealer F4 Express

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Leak Sealer F4 Express
Product code : 59903
Product description : Not available.
Product type : Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Supplier	: Alpha, Alent plc Forsyth Road Sheerwater Woking Surrey England GU21 5RZ Tel: +44(0)1483 758400 Fax: +44(0)1483 728837	Manufacturer	: Alpha, Alent plc Forsyth Road Sheerwater Woking Surrey England GU21 5RZ Tel: +44(0)1483 758400 Fax: +44(0)1483 728837
-----------------	---	---------------------	---

Contact person : shosken@alent.com

Emergency phone:

Material uses : Water-boiler treatment.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Directive 1999/45/EC [DPD]

Europe

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F+; R12

Physical/chemical hazards : Extremely flammable.

Denmark

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F+; R12

Physical/chemical hazards : Extremely flammable.

Norway

Date of issue/Date of revision : 25/04/2014.

1/17

SECTION 2: Hazards identification

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F+; R12

Physical/chemical hazards : Extremely flammable.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard symbol or symbols :



Indication of danger : Extremely flammable

Risk phrases : R12- Extremely flammable.

Safety phrases : S2- Keep out of the reach of children.
S16- Keep away from sources of ignition - No smoking.
S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Hazardous ingredients :

Supplemental label elements : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
Austria					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Belgium					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Bulgaria					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Croatia					

SECTION 3: Composition/information on ingredients

butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Denmark					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Estonia					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Finland					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
France					
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Germany					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Greece					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Hungary					
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Ireland					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Latvia					

Leak Sealer F4 Express

SECTION 3: Composition/information on ingredients

propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Norway					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Poland					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Portugal					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Romania					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Slovenia					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Spain					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Switzerland					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Turkey					
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]

SECTION 3: Composition/information on ingredients

United Kingdom (UK)					
butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : May cause eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause skin irritation.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Leak Sealer F4 Express

SECTION 4: First aid measures

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the

SECTION 6: Accidental release measures

same hazard as the spilled product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

- Recommendations** : Not available.

- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
<p>Europe</p> <p>☒ No exposure limit value known.</p> <p>Austria</p>	

SECTION 8: Exposure controls/personal protection

propane	GKV_MAK (Austria, 12/2011). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. CEIL: 2000 ppm, 3 times per shift, 60 minutes. CEIL: 3600 mg/m ³ , 3 times per shift, 60 minutes.
butane	GKV_MAK (Austria, 12/2011). TWA: 800 ppm 8 hours. CEIL: 3800 mg/m ³ , 3 times per shift, 60 minutes. CEIL: 1600 ppm, 3 times per shift, 60 minutes. TWA: 1900 mg/m ³ 8 hours.
Belgium	
propane	Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 1000 ppm 8 hours. Form: gas
butane	Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 1000 ppm 8 hours. Form: gas
Bulgaria	
propane	България Министерство на труда и социалната политика и Министерството на здравеопазването (Bulgaria, 1/2012). Limit value 8 hours: 1800 mg/m ³ 8 hours.
butane	България Министерство на труда и социалната политика и Министерството на здравеопазването (Bulgaria, 1/2012). Limit value 8 hours: 1900 mg/m ³ 8 hours.
Croatia	
butane	MinGoRP GVI/KGVI (Croatia, 1/2009). ELV: 22 mg/m ³ 8 hours. ELV: 10 ppm 8 hours. STELV: 1810 mg/m ³ 15 minutes. STELV: 750 ppm 15 minutes.
Czech Republic	
No exposure limit value known.	
Denmark	
propane	Arbejdstilsynet (Denmark, 10/2012). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
butane	Arbejdstilsynet (Denmark, 10/2012). TWA: 500 ppm 8 hours. TWA: 1200 mg/m ³ 8 hours.
Estonia	
propane	Sotsiaalminister (Estonia, 10/2007). TWA: 1800 mg/m ³ 8 hours. TWA: 1000 ppm 8 hours.
butane	Sotsiaalminister (Estonia, 10/2007). TWA: 1500 mg/m ³ 8 hours. TWA: 800 ppm 8 hours.
Finland	
propane	Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 12/2011). TWA: 800 ppm 8 hours. TWA: 1500 mg/m ³ 8 hours. STEL: 1100 ppm 15 minutes. STEL: 2000 mg/m ³ 15 minutes.
butane	Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 12/2011). STEL: 1000 ppm 15 minutes. TWA: 800 ppm 8 hours.
France	

SECTION 8: Exposure controls/personal protection

butane	Ministère du travail (France, 7/2012). Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits TWA: 800 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours.
Germany	
propane	TRGS900 AGW (Germany, 9/2012). TWA: 1800 mg/m ³ 8 hours. PEAK: 7200 mg/m ³ 15 minutes. TWA: 1000 ppm 8 hours. PEAK: 4000 ppm 15 minutes.
butane	TRGS900 AGW (Germany, 9/2012). TWA: 2400 mg/m ³ 8 hours. PEAK: 9600 mg/m ³ 15 minutes. TWA: 1000 ppm 8 hours. PEAK: 4000 ppm 15 minutes.
Greece	
propane	Υπουργείο Εργασίας και Κοινωνικών Υποθέσεων (Greece, 2/2012). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
butane	Υπουργείο Εργασίας και Κοινωνικών Υποθέσεων (Greece, 2/2012). TWA: 1000 ppm 8 hours. TWA: 2350 mg/m ³ 8 hours.
Hungary	
butane	25/2000. (IX. 30.) EüM-SzCsM együttes rendelet (Hungary, 12/2011). TWA: 2350 mg/m ³ 8 hours. PEAK: 9400 mg/m ³ 15 minutes.
Ireland	
propane	NAOSH (Ireland, 5/2010). Oxygen Depletion [Asphyxiant]. OELV-8hr: 1000 ppm 8 hours.
butane	NAOSH (Ireland, 5/2010). OELV-8hr: 1000 ppm 8 hours.
Italy	
No exposure limit value known.	
Latvia	
propane	Ministru kabineta - AER (Latvia, 2/2011). TWA: 100 mg/m ³ , (as C) 8 hours. STEL: 300 mg/m ³ , (as C) 15 minutes.
butane	Ministru kabineta - AER (Latvia, 2/2011). TWA: 300 mg/m ³ 8 hours.
Lithuania	
No exposure limit value known.	
Netherlands	
No exposure limit value known.	
Norway	
propane	Arbeidstilsynet (Norway, 12/2011). TWA: 500 ppm 8 hours. TWA: 900 mg/m ³ 8 hours.
butane	Arbeidstilsynet (Norway, 12/2011). TWA: 250 ppm 8 hours. TWA: 600 mg/m ³ 8 hours.
Poland	

SECTION 8: Exposure controls/personal protection

propane	Rozporządzenie Ministra Pracy i Polityki Społecznej (Dz. U. 2002 Nr 217, poz. 1833, z późn. zm.) (Poland, 12/2011). TWA: 1800 mg/m ³ 8 hours.
butane	Rozporządzenie Ministra Pracy i Polityki Społecznej (Dz. U. 2002 Nr 217, poz. 1833, z późn. zm.) (Poland, 12/2011). TWA: 1900 mg/m ³ 8 hours. STEL: 3000 mg/m ³ 15 minutes.
Portugal	
propane	Instituto Português da Qualidade (Portugal, 3/2007). TWA: 1000 ppm 8 hours.
butane	Instituto Português da Qualidade (Portugal, 3/2007). TWA: 1000 ppm 8 hours. Form: gas TWA: 1000 ppm 8 hours.
Romania	
propane	Ministerul Muncii, Familiei si Protectiei Sociale și Ministerul Sănătății (Romania, 1/2012). VLA: 1400 mg/m ³ 8 hours. VLA: 778 ppm 8 hours. Short term: 1800 mg/m ³ 15 minutes. Short term: 1000 ppm 15 minutes.
Slovakia	
No exposure limit value known.	
Slovenia	
propane	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Slovenia, 12/2010). TWA: 1800 mg/m ³ 8 hours. TWA: 1000 ppm 8 hours. KTV: 7200 mg/m ³ , 4 times per shift, 15 minutes. KTV: 4000 ppm, 4 times per shift, 15 minutes.
butane	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Slovenia, 12/2010). TWA: 2400 mg/m ³ 8 hours. TWA: 1000 ppm 8 hours. KTV: 9600 mg/m ³ , 4 times per shift, 15 minutes. KTV: 4000 ppm, 4 times per shift, 15 minutes.
Spain	
propane	INSHT (Spain, 1/2012). TWA: 1000 ppm 8 hours. Form: gas
butane	INSHT (Spain, 1/2012). TWA: 1000 ppm 8 hours. Form: gas
Sweden	
No exposure limit value known.	
Switzerland	
propane	SUVA (Switzerland, 1/2013). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours. STEL: 4000 ppm 15 minutes. STEL: 7200 mg/m ³ 15 minutes.
butane	SUVA (Switzerland, 1/2013). TWA: 800 ppm 8 hours. TWA: 1900 mg/m ³ 8 hours. STEL: 7200 mg/m ³ 15 minutes. STEL: 3200 ppm 15 minutes.
Turkey	

SECTION 8: Exposure controls/personal protection

propane	NIOSH REL (United States, 1/2013). TWA: 1000 ppm 10 hours.
butane	TWA: 1800 mg/m ³ 10 hours. NIOSH REL (United States, 1/2013). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours.
United Kingdom (UK)	
butane	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 1810 mg/m ³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): disposable vinyl

SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: None assigned.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: None assigned.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Liquid.
- Color** : White.
- Odor** : Not available.
- pH** : 7.6 [Conc. (% w/w): 5%]
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flash point** : Not available.
- Upper/lower flammability or explosive limits** : Not available.
- Relative density** : 1.012
- Solubility(ies)** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- :
- VOC content** : 105.4 % (w/w)

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

SECTION 10: Stability and reactivity

10.5 Incompatible materials : Highly reactive or incompatible with the following materials:
oxidizing materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : May cause skin irritation.

Eye contact : May cause eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

Ingestion : No specific data.

Skin contact : No specific data.

Eye contact : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Leak Sealer F4 Express

SECTION 11: Toxicological information

- Teratogenicity** : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

- Conclusion/Summary** : Not available.

12.2 Persistence and degradability

- Conclusion/Summary** : Not available.

12.3 Bioaccumulative potential

- Not available.

12.4 Mobility in soil

- Soil/water partition coefficient (K_{oc})** : Not available.
Mobility : Not available.

12.5 Results of PBT and vPvB assessment

- PBT** : Not applicable.
vPvB : Not applicable.

- 12.6 Other adverse effects** : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste product residues should not be disposed of via the sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

European waste catalogue (EWC)



Waste code	Waste designation
16 03 04	inorganic wastes other than those mentioned in 16 03 03

Packaging

SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number	1950	1950
14.2 UN proper shipping name	Aerosols, flammable (propane, Butane)	Aerosols, flammable (propane, Butane)
14.3 Transport hazard class(es)	2 	2.1 
14.4 Packing group	-	-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Europe inventory : Not determined.

National regulations

Austria

Belgium

Bulgaria

Croatia

Czech Republic

Denmark

Estonia

Finland

France

Germany

Hazard class for water : 1 Appendix No. 4

Greece

Hungary

Ireland

SECTION 15: Regulatory information[Italy](#)[Latvia](#)[Lithuania](#)[Netherlands](#)[Norway](#)[Poland](#)[Portugal](#)[Romania](#)[Slovakia](#)[Slovenia](#)

Product/ingredient name	List name	Name on list	Classification	Notes
butane	Slovenia Carcinogen, Mutagen, Reprotoxic chemicals	butan z vsebnostjo >= 0,1% butadiena [203-450-8]	Carc.1, Muta. MUTA2	-

[Spain](#)[Sweden](#)[Switzerland](#)[Turkey](#)[United Kingdom \(UK\)](#)

Product/ingredient name	List name	Name on list	Classification	Notes
butane	UK Occupational Exposure Limits EH40 - WEL	butane	Carc.	-

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Date of printing : 01/10/2014.

Date of issue/ Date of revision : 25/04/2014.

Date of previous issue : 24/04/2014.

Version : 1.6

Notice to reader

☑ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**Classification****Justification**

Not classified.

Europe

Full text of abbreviated H statements : ☑ Not applicable.

Leak Sealer F4 Express

Full text of classifications [CLP/GHS] : Not applicable.

Full text of abbreviated R phrases : R12- Extremely flammable.

Full text of classifications [DSD/DPD] : F+ - Extremely flammable

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

an Alent plc Company