

# MATERIAL SAFETY DATA SHEET

## SECTION 1 – PRODUCT INFORMATION

**Supplier Name**

The Mill-Rose Company  
7310 Corporate Blvd.  
Mentor, OH 44060

**Emergency Telephone No.**

(800) 321-3598

**Date Prepared:** April 1, 2012

Replaces: June, 2007

**Product**

Gas Line Thread Seal Tape  
With PTFE

**Trade Names and Synonyms**

3-Wrap Yellow Gas Tape

## SECTION 2 – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

| Ingredients             | OSHA PEL | CAS Number | ACGIH TLV |
|-------------------------|----------|------------|-----------|
| Polytetrafluoroethylene | N/A      | 9002-84-0  | N/A       |
| Petroleum Solvent       | N/A      | 64742-47-8 | N/A       |
| Pigment                 | N/A      | N/A        | N/A       |

## SECTION 3 – PHYSICAL/CHEMICAL CHARACTERISTICS

**Boiling Point:** N/A

**Specific Gravity (H<sub>2</sub>O=1):** 2.1

**Vapor Pressure (mm Hg):** N/A

**Melting Point:** N/A

**Vapor Density (air=1):** N/A

**Evaporation Rate (Butyl Acetate=1):** N/A

**Solubility in Water:** Insoluble

**Appearance and Odor:** Yellow polymeric film/odorless

## SECTION 4 – FIRE AND EXPLOSION HAZARD DATA

**Flash Point (Method Used):** N/A

**Flammable Limits:** N/A

**Extinguishing Media:** Any standard medium

**Special Fire Fighting Procedures:** Combustible solid. Will burn if in contact with flame.

Combustion ceases when flame is removed. Decomposition on heating above 260°C results in the emission of toxic fumes. Fire fighters to wear self contained breathing apparatus if there is a risk of exposure to products of combustion and decomposition.

**Unusual Fire and Explosion Hazards:** Toxic fumes given off above 260°C

## SECTION 5 – REACTIVITY DATA

**Conditions to Avoid:** Temperatures above 260°C without adequate ventilation

**Incompatibility (Materials to avoid):** Alkali metals, extremely potent oxidizers (e.g. fluorine, chlorine tri- fluoride), 80% NaOH or KOH, metal hydrides such as boranes (e.g. B<sub>2</sub>H<sub>6</sub>), Aluminum chloride, ammonia, certain amines (R-NH<sub>2</sub>) imines (RH-NH) and 70% nitric acid at temperatures near 260°C. Do not use on oxygen lines.

**SECTION 6 – HEALTH HAZARD DATA**

**Health Hazards (Acute):**

**Swallowed:** No adverse effect known

**Eye:** See above

**Skin:** See above

**Inhalation:** The material is not normally an inhalation hazard at temperatures below 260°C as it remains an inert solid. However, exposure to thermal degradation products at temperatures above 260°C or fumes from tobacco contaminated with particles of the product may result in “Polymer Fume Fever” or influenza-like symptoms (chills, headaches, difficulty in breathing and fever). Symptoms may appear several hours after exposure but will disappear within 24-48 hours. There are exposure standards for decomposition products.

|     | TWA |       | STEL            |       |
|-----|-----|-------|-----------------|-------|
| HF* | ppm | mg/m3 | ppm             | mg/m3 |
|     | 3   | 2.6   | Peak Limitation |       |

\*Measured as an inspirable fraction

Carbonyl fluoride is the main decomposition product formed when PTFE is subjected to extended exposure at normal sintering temperatures (400°C). Carbonyl fluoride is immediately converted to highly corrosive hydrogen fluoride in the presence of moist air.

**Health Hazards (Chronic):** No adverse effects known.

**Toxicity:** No LD50 data is available on PTFE. No toxicity was observed in male/female rats when fed PTFE (up to 25%) for 90 days. Local sarcomas were induced in mice and rats implanted subcutaneously or intraperitoneally with PTFE. However, this is not considered relevant to normal industrial usage.

**Carcinogenicity:** PTFE has been classified by the International Agency for Research into Cancer as a group III agent. As such it is not classifiable as to its carcinogenicity to humans.

**Emergency and First Aid Procedures:** Inhalation: Remove victim from exposure – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing labored and patient cyanotic (blue) ensure that airways are clear and have a qualified person give oxygen through a face mask. If breathing has stopped apply artificial respiration at once. In event of cardiac arrest apply external cardiac massage. Seek medical advice.

**SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to be taken in case material is released or spilt:** Sweep up

**Waste Disposal Method:** Burning is not recommended. Comply with local regulations

**Precautions to be taken in Handling and Storage:** Keep away from flames. Store below 260°C

**SECTION 8 – CONTROL MEASURES**

**Respiratory Protection:** No special controls are necessary if used within recommended operation temperatures (ie -260°C to +260°C).

**Ventilation:** See above

**Protective Gloves:** See above

**Eye Protection:** See above

**Other Protective Clothing or Equipment:** See above

**Work/Hygienic Practices:** See above

**NOTICE FROM THE MILL-ROSE COMPANY**

*The information in this Material Safety Data Sheet (MSDS) relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. We believe that the information contained herein is current as of the date of the MSDS. Since use of this information and these opinions and the conditions of use of the product are not within the control of The Mill-Rose Company, it is the user's obligation to determine the conditions of safe use of the product.*