

1. Product and Company Identification

Product identifier	TRI-POW'R HD COIL CLEANER AEROSOL (4371-75)
Other means of identification	Not available
Recommended use	Heavy Duty Cleaner/Degreaser
Recommended restrictions	None known.
Manufacturer information	Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Gases under pressure	Liquefied gas
	Corrosive to metals	Category 1
Health hazards	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word Danger

Hazard statement Contains gas under pressure; may explode if heated. May be corrosive to metals. Causes severe skin burns and eye damage.

Precautionary statement

Prevention Keep only in original packaging. Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response Absorb spillage to prevent material-damage. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage Protect from sunlight. Store in a well-ventilated place. Store in a corrosion resistant container with a resistant inner liner. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	1-5
Potassium hydroxide		1310-58-3	1-5

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	1-5
Silicic acid, sodium salt		1344-09-8	1-5
Sodium carbonate		497-19-8	1-5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Specific treatment (see information on this label).
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
Ingestion	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and chemical splash goggles. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Foam. Carbon dioxide. Dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. Firefighters should wear a self-contained breathing apparatus.
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self-contained breathing apparatus.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use only with adequate ventilation. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Do not re-use empty containers. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate or crush. This material can accumulate static charge which may cause spark and become an ignition source. Store in a corrosion resistant container with a resistant inner liner. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

8. Exposure Controls/Personal Protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1000 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m ³
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	750 ppm
	TWA	600 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m ³
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m ³

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	800 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m ³
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Potassium hydroxide (CAS 1310-58-3)	TWA	2 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Chemicals listed in section 3 that are not listed here do not have established limit values for ACGIH or OSHA PEL.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection**Hand protection**

Impervious gloves. Confirm with reputable supplier first.

Other

Wear appropriate chemical resistant clothing. As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards

Not applicable.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Aerosol.
Physical state	Gas.
Form	Aerosol
Color	Orange
Odor	Pine
Odor threshold	Not available.

pH	13.3 (Concentrate)
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C)
Pour point	Not available.
Specific gravity	1.13
Partition coefficient (n-octanol/water)	Not available
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	UN Manual of Tests & Criteria, Part 3, Section 31.5 - Enclosed Space Ignition Test The finished product is not expected to be flammable as per test data.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available
Flammability limit - upper (%)	Not available
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available
Vapor density	Not available
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and Reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents. May be corrosive to metals.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Heat. Do not mix with other chemicals.
Incompatible materials	Strong oxidizing agents. Metals.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.
Information on likely routes of exposure	
Ingestion	Causes digestive tract burns. May cause stomach distress, nausea or vomiting.
Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns.
Eye contact	Causes serious eye damage.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Information on toxicological effects	
Acute toxicity	Causes burns.

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 680 mg/L, 2 Hours, HSDB 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 800000 ppm, 10 Minutes, ECHA 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 276000 ppm, 4 Hours, CCOHS 1443 mg/L, 10 Minutes, ECHA 1355 mg/L, 10 Minutes
<i>Oral</i>		
LD50	Not available	
Potassium hydroxide (CAS 1310-58-3)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	388 mg/kg, ECHA 365 mg/kg, ECHA 333 mg/kg, ECHA 273 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours > 800000 ppm, 10 Minutes, ECHA > 1464 mg/L, 15 Minutes, HSDB 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 1355 mg/L, 10 Minutes

Components	Species	Test Results
<i>Oral</i> LD50	Not available	
Silicic acid, sodium salt (CAS 1344-09-8)		
Acute		
<i>Dermal</i> LD50	Rat	> 5000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i> LC50	Rat	> 2.1 mg/L, 4 Hours, ECHA
<i>Oral</i> LD50	Mouse	1100 mg/kg, Toxic and Hazardous Industrial Chemicals Safety Manual. Tokyo, Japan
	Rat	5150 mg/kg, ECHA 3400 mg/kg, ECHA 1.1 g/kg, HSDB
Sodium carbonate (CAS 497-19-8)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg, ECHA
	Rat	> 2000 mg/kg, ECHA
<i>Inhalation</i> LC50	Guinea pig	800 mg/m ³ , 2 Hours, ECHA
	Mouse	1200 mg/m ³ , 2 Hours, ECHA
	Rat	2300 mg/m ³ , 2 Hours, ECHA 2.3 mg/L, 2 Hours, HSDB
<i>Oral</i> LD50	Rat	4090 mg/kg, RTECS 2800 mg/kg, ECHA, HSDB
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irritant		
Potassium hydroxide (CAS 1310-58-3)		Irritant
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	Not classified.	
Carcinogenicity	Not classified. See below.	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	Not classified.	
Teratogenicity	Not classified.	
Specific target organ toxicity - single exposure	Not classified.	

Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components	Species	Test Results
Potassium hydroxide (CAS 1310-58-3)		
Aquatic		
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>) 80 mg/L, 96 hours
Silicic acid, sodium salt (CAS 1344-09-8)		
Aquatic		
Crustacea	EC50	Water flea (<i>Ceriodaphnia dubia</i>) 0.28 - 0.57 mg/L, 48 hours
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>) 1800 mg/L, 96 hours
Sodium carbonate (CAS 497-19-8)		
Crustacea	EC50	Daphnia 265 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (<i>Ceriodaphnia dubia</i>) 156.6 - 298.9 mg/L, 48 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 300 mg/L, 96 hours

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Mobility in general	Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel] The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.
General	IMDG Regulated Marine Pollutant.

IATA:
Aerosols, non-flammable, containing substances in Class 8, Packing Group II, Forbidden

U.S. Department of Transportation (DOT)

Basic shipping requirements:


UN number	UN1950
Proper shipping name	Aerosols, corrosive, Packing Group II or III, (each not exceeding 1 L capacity).
Hazard class	Limited Quantity - US
Special provisions	A34
Packaging exceptions	<1L - Limited Quantity

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1950
Proper shipping name	AEROSOLS, non-flammable, containing substances in Class 8, packing group II
Hazard class	Limited Quantity - Canada
Special provisions	80
Packaging exceptions	<1L - Limited Quantity

DOT; TDG



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Butane (CAS 106-97-8) 1 TONNES
Propane (CAS 74-98-6) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8) Listed.
Potassium hydroxide (CAS 1310-58-3) Listed.
Propane (CAS 74-98-6) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)

**Clean Water Act (CWA)
Section 112(r) (40 CFR
68.130)**

Hazardous substance

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Butane (CAS 106-97-8) Listed.
Potassium hydroxide (CAS 1310-58-3) Listed.

US - Illinois Chemical Safety Act: Listed substance

Butane (CAS 106-97-8)
Potassium hydroxide (CAS 1310-58-3)
Propane (CAS 74-98-6)

US - Louisiana Spill Reporting: Listed substance

Butane (CAS 106-97-8) Listed.
Potassium hydroxide (CAS 1310-58-3) Listed.
Propane (CAS 74-98-6) Listed.

US - Minnesota Haz Subs: Listed substance

Butane (CAS 106-97-8) Listed.
Potassium hydroxide (CAS 1310-58-3) Listed.
Propane (CAS 74-98-6) Listed.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8)
Potassium hydroxide (CAS 1310-58-3)
Propane (CAS 74-98-6)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Propane (CAS 74-98-6)

US - Texas Effects Screening Levels: Listed substance

Butane (CAS 106-97-8) Listed.
Potassium hydroxide (CAS 1310-58-3) Listed.
Propane (CAS 74-98-6) Listed.
Silicic acid, sodium salt (CAS 1344-09-8) Listed.
Sodium carbonate (CAS 497-19-8) Listed.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)
Potassium hydroxide (CAS 1310-58-3)
Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)
Potassium hydroxide (CAS 1310-58-3)
Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)
Potassium hydroxide (CAS 1310-58-3)
Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 3
FLAMMABILITY	0
PHYSICAL HAZARD	1
PERSONAL PROTECTION	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document. The information in the sheet was written based on the best knowledge and experience currently available.

Issue date

10-November-2017

Version

02

Effective date

10-November-2017

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.