MATERIAL SAFETY DATA SHEET

HMIS CODES: H F R P
2 1 0 B

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements. U.S. Department of Labor Occupational Safety and Health Administrator (Non-Mandatory Form) Form Approved OMB No. 1218-0072

must be consulted for specific requirem	Form Approved OMB No. 1218-0072				
IDENTITY (AS USED ON LABEL AND STEEL-UNYTE THREAD AND GASK	NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.				
Section I					
Manufacturer's Name: J.C. WHITLAM MANUFACTURING CO	Emergency Telephone Number: (330) 334 - 2524				
Address (Number, Street, City, State, a 200 WEST WALNUT STREET	Telephone Number for Information: (330) 334 - 2524				
P.O. BOX 380	Date Prepared: January 24, 2014				
WADSWORTH, OHIO 44282-0380	Signature of Preparer (optional):				
Section II - Hazardous Ingredients/Id	lentity Information				
HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY: CC	OSHA PEL	ACGIH TLV	OTHER LIMITS Recommended	% (optional)	
ISOPROPYL ALCOHOL [CAS#67-63-0	N/A	500 ppm	N/A	18 - 23	
Section III - Physical/Chemical Chara	acteristics	1			
Boiling Point:	N/A	Specific Gravity (H20 =1):			1.35
Vapor Pressure (mm Hg):	44	Melting Point:			N/A
Vapor Density (AIR = 1):	1	Evaporation Rate (Butyl Acetate = 1):			1.9
Solubility in Water:	SLIGHT	SLIGHT VOC Content:			
Appearance and Odor: DARK GRAY S	SEMI-PASTE - SLIGH	HT ALCOHOL	ODOR		
Section IV - Fire and Explosion Haza	rd Data			-	
Flash Point (Method Used): 58°F(TCC)	Flammable Limits: 921°F (494°C) IGN	UEL: 1.9%			
Extinguishing Media: CARBON DIOXID	DE OR DRY CHEMIC	CAL			
Special Fire Fighting Procedures: USE	RESPIRATORY PE	ROTECTION.			
Unusual Fire and Explosion Hazards: 0 FLAME. DO NOT APPLY TO HOT SU		TURE. DO N	OT USE NE	AR HEAT, SPARKS	OR OPEN

Section V - Reactivity Data				STEEL-UNYTE THREAD AND GASKET SEALER ST					
Stability:		Unstable:			Conditions to Avoid: N/A				
		Stable:		Χ					
Incompatibility (Materials to Avoid): LIQUID OXYGEN SYSTEMS.									
Hazardous Decomposition or Byproducts: N/A									
Hazardous Polymerization:		May Occur:			Conditions to Avoid: N	√A			
		Will Not Occur:		Χ					
Section VI - Health Hazard Data									
Route(s) of Entry:	Inhalatio	on? YES Sk		Skin? YES		Ingestion? YES			
Health Hazards (Acute and Chronic): N/A									
Carcinogenicity:	NTP?	NO IA		IARC Monographs? NO		OSHA Regulated? NO			
Signs and Symptoms of Exposure: INHALATION: POSSIBLE DIZZINESS IF USED IN CONFINED AREAS. SKIN: MAY CAUSE MILD IRRITATION TO SENSITIVE SKIN. INGESTION: WILL CAUSE NAUSEA AND DIZZINESS.									
Medical Conditions Generally Aggravated by Exposure: N/A									
Emergency and First Aid Procedures: EYE CONTACT: FLUSH EYES WITH WATER AND CONTACT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. INHALATION: MOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN.									
Section VII - Precautions for Safe Handling and Use									
Steps to Be Taken in Case Material is Released or Spilled: CONFINE SPILL AND USE NORMAL GOOD HOUSEKEEPING PROCEDURES.									
Waste Disposal Method: DISPOSAL TO BE DONE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.									
Precautions to Be Taken in Handling and Storing: STORE AWAY FROM HEAT OR OPEN FLAME. CLOSE CONTAINER AFTER EACH USE.									
Other Precautions: WEAR PROTECTIV OF REACH OF CHI		ES TO PREVEN	NT PC	OSSIBLE	SKIN ABSORPTION AI	ND DERMATITIS. KEEP OUT			
Section VIII - Contr	ol Measu	res							
Respiratory Protection			N A C	CONFINE	D AREA, A RESPIRAT	OR MAY BE NECESSARY.			
Ventilation:	Local Ex	Local Exhaust: NORMAL VI		/ENTILATION IS ADEQUATE.		Special: N/A			
	Mechan	Mechanical (General): N/A				Other: N/A			
GLOVES MAY BE NECESSARY FOR KEE			Protection: POUT OF EYES. WEAR PROTECTIVE GOGGLES WHERE DESSARY.						
Other Protective Clothing or Equipment: N/A									
Work/Hygienic Practices: N/A									