GENUINE

Tigerloop®

For use as oil burner pump suction and return lines (not for nozzle line)

FLEXIBLE OIL LINES



For swing-out doors and oil de-aerators

Steel Braided Covering - 24" and 36" Long - 145 PSI - 200 °F For No. 1 and 2 heating oil, BioHeat® B20 or B100

FLEXIBLE OIL LINES, Standard

TELXIBLE OIL LINES, Standard			
P No.	Description	BioFuels Rating	
\$220-24 \$220-36 \$220-40 \$222-36	Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 24" long Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 36" long Replacement fitting for flexible oil line, 3/8" inv. flare x 1/4"-NPT Flexible oil line, braided steel covering, 3/8" Flare (FxF), 36" long	biofuels ™ COMPATIBLE B20 SEE STATEMENT ON INSIDE COVER	
S223-24 S223-36	BioFuels Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 24" long BioFuels Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 36" long	Diofuels COMPATIBLE B100 SEE STATEMENT ON INSIDE COVER	



FLEXIBLE OIL LINES

SPECIAL FOR RIELLO

Color coded Red & Blue for easy identification

European thread connects to **RIELLO** pump adaptor

Easy installation & service with two piece swivel connector



FLEXIBLE OIL LINES, Special for RIELLO burners

-W/		
P No.	Description	BioFuels Rating
S221-24 S221-36	Flexible oil line for Riello burner, braided steel outside covering, 1/4"- NPT (M) x 1/4"- BSPP (RIELLO pump adapter thread), 24" long Flexible oil line for Riello burner, braided steel outside covering, 1/4"- NPT (M) x 1/4"- BSPP (RIELLO pump adapter thread), 36" long	B20 SEE STATEMENT ON INSIDE COVER

Service Advisory: All flexible oil lines should be inspected annually for deterioration (i.e. stiffness, cracks, etc.) and replaced every 3 years

