

ProPEX® Lead-free (LF) Brass Ball Valve

Submittal Information

Revision A: Jan. 20, 2010

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Material: C69300 Brass

Maximum Temperature (no pressure): 250°F (121°C)

Maximum Working Pressure: 250 psi

Product Information and Application Use

Use the Uponor ProPEX® Lead-free Brass Ball Valve for all plumbing and radiant heating applications.¹

Both ends are manufactured with the ProPEX Fitting for connections to Uponor AquaPEX® tubing or Wirsbo hePEX™ tubing. These valves are not compatible with applications using glycol.



✓	Description	Part Number	Length	Width	Weight
	ProPEX LF Brass Ball Valve (large bore), ½" PEX x ½" PEX	LF4815050	2.75"	1.62"	0.28 lbs.
	ProPEX LF Brass Ball Valve (large bore), ¾" PEX x ¾" PEX	LF4817575	3.37"	1.67"	0.30 lbs.
	ProPEX LF Brass Ball Valve (full port), ¾" PEX x ¾" PEX	LF4827575	5.11"	2.60"	0.40 lbs.
	ProPEX LF Brass Ball Valve (full port), 1" PEX x 1" PEX	LF4821010	5.99"	3.08"	0.45 lbs.

Installation

Install valve according to local building code. Do not dismantle. Refer to the AquaPEX Professional Plumbing Installation Guide or the Radiant Floor Heating Installation Handbook for additional information.

Standards

CSA B137.5 and B125; ASTM F877; ASTM F1960; ASME A112.18.1

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

ANSI/NSF 14- and 61-certified; U.P. Code, Annex G

Related Applications

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems
Snow and Ice Melting Systems
Permafrost Protection Systems
Turf Conditioning Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-1409
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.