



CON-STAB ID SEAL® Full Couplings

| PE SIZE | WALL | PART NUMBER (3408/4710) |
|------------------------|-----------------|----------------------------|
| 1/2" CTS (5/8" OD) | .090 | 3259-52-1004-00†‡ |
| 3/4" CTS (7/8" OD) | .090 | 3259-52-1006-00‡ |
| 1" CTS (1 1/8" OD) | .099/.101 | 3259-52-1008-00†‡ |
| | .090 | 3259-52-1008-AA‡ |
| 1 1/4" CTS (1 3/8" OD) | .090 | 3259-52-1039-AA |
| 1/2" IPS | SDR-9.33 (.090) | 3259-52-1012-00‡ |
| 3/4" IPS | SDR-11 (.095) | 3259-52-1013-00†‡ |
| 1" IPS | SDR-11 (.119) | 3259-52-1014-00†‡ |
| 1 1/4" IPS | SDR-10 (.166) | 3259-52-1015-00†‡ |
| | SDR-11 (.151) | 3259-52-1015-AA |
| 1 1/2" IPS | SDR-11 (.173) | 3259-52-1016-00†‡ |
| 2" IPS | SDR-11 (.216) | 3259-52-1017-00†‡ |



- **For sizes not listed, contact Continental Industries.**
- Pressure rating—Designed to meet or exceed pressure rating of PE pipe per 49 CFR Part 192 and ASTM D2513.
- Recommended accessories;
 - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.
- For Con-Stab ID Seal® Couplings with EFV's, contact Continental Industries.
- † = CSA Approved / ‡ = IAPMO/UPC Listed

CON-STAB ID SEAL® End Caps

| PE SIZE | WALL | PART NUMBER (3408/4710) |
|------------------------|-----------------|----------------------------|
| 1/2" CTS (5/8" OD) | .090 | 3259-53-1004-00†‡ |
| 3/4" CTS (7/8" OD) | .090 | 3259-53-1006-00‡ |
| 1" CTS (1 1/8" OD) | .099/.101 | 3259-53-1008-00†‡ |
| | .090 | 3259-53-1008-0A‡ |
| 1 1/4" CTS (1 3/8" OD) | .090 | 3259-53-1039-0A |
| 1/2" IPS | SDR-9.33 (.090) | 3259-53-1012-00‡ |
| 3/4" IPS | SDR-11 (.095) | 3259-53-1013-00†‡ |
| 1" IPS | SDR-11 (.119) | 3259-53-1014-00†‡ |
| 1 1/4" IPS | SDR-10 (.166) | 3259-53-1015-00†‡ |
| | SDR-11 (.151) | 3259-53-1015-0A |
| 1 1/2" IPS | SDR-11 (.173) | 3259-53-1016-00†‡ |
| 2" IPS | SDR-11 (.216) | 3259-53-1017-00†‡ |



- **For sizes not listed, contact Continental Industries.**
- Pressure rating—Designed to meet or exceed pressure rating of PE pipe per 49 CFR Part 192 and ASTM D2513.
- Recommended accessories;
 - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.
- † = CSA Approved / ‡ = IAPMO/UPC Listed

CON-STAB ID SEAL® Cap-N-Go Couplings

| PE SIZE | WALL | PART NUMBER (3408/4710) |
|--------------------|-----------------|----------------------------|
| 1/2" CTS (5/8" OD) | .090 | 3259-57-1004-00‡ |
| 1" CTS (1 1/8" OD) | .099/.101 | 3259-57-1008-00‡ |
| | .090 | 3259-57-1008-AA |
| 1/2" IPS | SDR-9.33 (.090) | 3259-57-1012-00‡ |
| 3/4" IPS | SDR-11 (.095) | 3259-57-1013-00‡ |
| 1" IPS | SDR-11 (.119) | 3259-57-1014-00‡ |
| 1 1/4" IPS | SDR-10 (.166) | 3259-57-1015-00‡ |
| | SDR-11 (.151) | 3259-57-1015-AA |
| 2" IPS | SDR-11 (.216) | 3259-57-1017-00‡ |



- **For sizes not listed, contact Continental Industries.**
- Pressure rating—Designed to meet or exceed pressure rating of PE pipe per 49 CFR Part 192 and ASTM D2513.
- Recommended accessories;
 - Continental's Bladed Chamfering Tool. See page 30 for size combinations available.
- ‡ = IAPMO/UPC Listed