





 RP19754▲	 RP34345▲	 RP43773 RP64196	 RP50783	 RP50815	 RP52216
 RP53349	 RP53998	 RP54977 RP64078	 RP61607	 RP61893	

Submitted Model No.: _____

Specific Features: _____

Part #	Description	Models
 RP19754	1.5 gpm aerator assy. 15/16"-27 male	100,101, 120, 140, 175, 300, 240, 340, 400, 440, 441 (DST & non-DST models) 172, 174, 185, 1903, 2100, 2176, 2274, 2276, 2400, 2476
 RP34345	1.5 gpm aerator assy. 3/4"-27 female	2155
 RP43773	1.5 gpm aerator insert	155, 156 (non-DST models) 100,140, 300, 240, 400, 440 (DST & non-DST models) 172, 174, 185, 2100, 2176, 2274, 2276, 2400, 2457, 2476
RP64196	2.2 gpm aerator insert	
RP50783	2.2 gpm aerator assy. M24x1 male	11946-SD (non-DST model) Wrench RP52217
RP50815	Full Flow aerator assy. M21.5 x1 male	4153, 4353, 9178, 9192, 9992, 16971, 19922, 19949, 19950, 19978, 19992 (DST models) Wrench Included
 RP52216	1.5 gpm aerator insert	119/319/419 (DST & non-DST models) 155/156 (DST models) 4380 DST models) Wrench RP52217
 RP53349	1.5 gpm jr. aerator assy. 13/16"-27 male	190/2190 2170/2171/2172
RP53998	2.2 gpm aerator assy. M24x1 male	155, 156, 1980, 1980T, 4380, 4380T, 11946-SD (DST models) Wrench RP52217
 RP54977	1.5 gpm aerator assy. 13/16"-27 male	1353, 3353, 4453, 11926 (DST models) Wrench RP52217
 RP61607	1.5 gpm adapter	467, 470, 473, 955, 978, 980, 980T, 989, 999, 4353, 9955, 9978 (DST models)
RP61893	2.2 gpm aerator assy. 15/16"-27 male	B1310LF, B3310LF, B4410LF
RP64078	2.2 gpm aerator assy. 13/16"-27 male	1353, 3353, 4453, 11926 (DST models) Wrench RP52217

▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-K-AERATORS Rev. C



WATER EFFICIENT KITCHEN AERATORS

STANDARD SPECIFICATIONS:

- Max. 1.50 gpm @ 60 psi, 5.7 L/min @ 414 kPa
- Max. 2.20 gpm @ 60 psi, 8.3 L/min @ 414 kPa
- Water efficient uses 30% less than industry standard of 2.2 gpm @ 60 PSI per ASME.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1



55 E. 111th Street, Indianapolis, Indiana 46280
350 South Edgeware Road, ST. Thomas, ON N5P 4C4
© 2015 Masco Corporation of Indiana