## For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

# LEAD FREE\* Series 35 Quick-Connect Elbows

Watts Quick-Connect Elbows are designed and manufactured for many years of trouble free service. Produced of off white Polysulfone, a high performance thermal plastic material, the Watts Quick-Connect design allows for quick and easy connections without the use of installation tools.

### **Specifications**

Connection shall be made using Watts Series 35 Quick-Connect fitting with Integral Collet and O-Ring guide. Fitting shall be able to fully rotate under pressure and allow for easy disconnect and reuse without the use of disconnection tools. Fitting must not disassemble to disconnect.

### Approvals

NSF-61, NSF-14, CSA B137.5, ASTM F877, UPC, ASSE 1061

### Ratings

100psi @ 180°F (6.8 bar @ 82°C) 250psi @ 75°F (17.3 bar @ 24°C)

### Example

3512-1008 35 = Series 35 12 = Type 12 Stackable Hose Barb Elbow 1008 = ½" CTS x ½" Barb

### **Dimensions – Weights**

Weight and Dimensions are approximate (tolerance +/- 1/8)

#### Type 12 Stackable Hose Barb Elbows

MODEL	SIZE & CONNECTION	ITEM I	LENGTH	ITEM H	IEIGHT	ITEM WEIGHT	
		A		В			
		in.	тт	in.	тт	lbs.	kg.
Package Type: Bulk							
3512-1008	1/2" CTS x 1/2"Barb	<b>1</b> ½	38	2 <sup>1</sup> /8	54	0.3	.14
Package Type: Poly Bag							
3512B-1008	1/2" CTS x 1/2"Barb	11/2	38	21/8	54	0.3	.14




**Caution:** The polysulfone material used in the Quick-Connect fittings can be compromised by exposure to volatile organic compounds (VOC's) and caustic chemicals. Therefore, **DO NOT** expose this product to any such chemical or foreign substance, which would include exposure to the following products: **Pipe Dopes (thread sealants),** bug sprays, lubricants, cleaners, paints, bleaches, acids, solder fluxes, plastic piping primers and cements, oxidizing agents, alkaline solutions, thinners, fuels, oil based caulks, hydrocarbons, spray foam of foaming agents (insulation).

3520

It is also recommended that all threaded connections be made with Teflon $\ensuremath{^{\circ}}$  tape only.

# \*The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.



3519



Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



A Watts Water Technologies Company

USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca

## Dimensions – Weights – Weight and Dimensions are approximate (tolerance +/ - 1/8)

### Type 17 Union Elbow

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM H	ITEM HEIGHT		/EIGHT
		A		В			
		in.	тт	in.	тт	lbs.	kg.
Package Type: Bul	k						
3517-08	3%" CTS	13⁄4	44	15/16	24	0.6	.27
3517-10	1⁄2" CTS	21/8	54	11/8	29	1	.45
3517-14	3⁄4" CTS	<b>2</b> <sup>11</sup> /16	68	13%	35	1.8	.81
3517-18	1" CTS	3	76	11/2	38	2.4	1.09
Package Type: Pol	y Bag						
3517B-08	3%" CTS	13⁄4	44	15/16	24	0.6	.27
3517B-10	1/2" CTS	21/8	54	11/8	29	1	.45
3517B-14	3⁄4" CTS	<b>2</b> <sup>11</sup> /16	68	13%	35	1.8	.81
3517B-18	1" CTS	3	76	11/2	38	2.4	1.09

### Type 18 Stackable Elbows

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM H	ITEM HEIGHT		EIGHT
		A		E	3		
		in.	тт	in.	mm	lbs.	kg.
Package Type: Bulk	(						
3518-08	3%" CTS	13/4	44	15/16	24	0.4	.18
3518-10	1/2" CTS	2	51	11/8	29	0.7	.32
3518-14	3⁄4" CTS	25/8	67	13/8"	35	0.8	.36
3518-18	1" CTS	3	76	13/4	45	1.9	.86
Package Type: Poly	Bag						
3518B-08	3%" CTS	13/4	44	<sup>15</sup> /16	24	0.4	.18
3518B-10	1⁄2" CTS	2	51	11/8	29	0.7	.32
3518B-14	3⁄4" CTS	25/8	67	13/8"	35	0.8	.36
3518B-18	1" CTS	3	76	13⁄4	45	1.9	.86

### Type 21 Drop Ear Elbows

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM HEIGHT		ITEM WEIGHT	
		A		В			
		in.	mm	in.	mm	lbs.	kg.
Package Type: Bul	k						
3521-1008	1/2" CTS x 1/2" NPT	21/8	54	<b>1</b> <sup>13</sup> ⁄16	46	1.1	.50
Package Type: Poly Bag							
3521B-1008	1/2" CTS x 1/2" NPT	21/8	54	<b>1</b> <sup>13</sup> ⁄16	46	1.1	.50

### Type 19 Male Elbow

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM HEIGHT		ITEM WEIGHT	
		A		В			
		in.	тт	in.	mm	lbs.	kg.
Package Type: Bu	lk						
3519-1006	1/2"CTS x 3/8"NPT	2	51	11/8	29	0.7	.32
3519-1008	1/2" CTS x 1/2"NPT	2	51	11/8	29	0.7	.32
3519-1816	1" CTS x 1"NPT	<b>2</b> <sup>3</sup> / <sub>4</sub>	70	13⁄4	45	1.9	.86
Package Type: Po	ly Bag						
3519B-1006	1/2"CTS x 3/8"NPT	2	51	11/8	29	0.7	.32
3519B-1008	1/2" CTS x 1/2"NPT	2	51	11/8	29	0.7	.32
3519B-1816	1" CTS x 1" NPT	23/4	70	13⁄4	45	1.9	.86

#### Type 20 Female Swivel Elbows

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM HEIGHT		ITEM W	EIGHT
		A		В			
		in.	mm	in.	mm	lbs.	kg.
Package Type: Bu	lk						
3520-0808	3/8" CTS x 1/2"NPS	2	51	15%	41	0.7	.32
3520-0813	3/8" CTS x 3/4"Closet	2	51	15%	41	0.8	.36
3520-1008	1/2" CTS x 1/2"NPS	<b>2</b> <sup>3</sup> ⁄16	56	2	51	1	.45
3520-1012	1/2" CTS x 3/4"NPS	<b>2</b> <sup>3</sup> ⁄16	56	2	51	1.2	.54
3520-1013	1/2" CTS x 3/4"Closet	<b>2</b> <sup>3</sup> ⁄16	56	2	51	1.1	.50
3520-1014	1/2" CTS x 3/4"FGHT	<b>2</b> <sup>3</sup> ⁄16	56	2	51	1	.45
Package Type: Pol	ly Bag						
3520B-0808	3/8" CTS x 1/2"NPS	2	51	15%	41	0.7	.32
3520B-0813	3/8" CTS x 3/4"Closet	2	51	15%	41	0.8	.36
3520B-1008	1/2" CTS x 3/4"NPS	<b>2</b> <sup>3</sup> /16	56	2	51	1	.45
3520B-1012	1/2" CTS x 3/4"NPS	<b>2</b> <sup>3</sup> /16	56	2	51	1.2	.54
3520B-1013	1/2" CTS x 3/4"Closet	<b>2</b> <sup>3</sup> /16	56	2	51	1.1	.50
3520B-1004	1/2" CTS x 3/4"FGHT	<b>2</b> <sup>3</sup> /16	56	2	51	1	.45

