

**HI-EFFICIENT DIRECT-VENT** 

## WALL FURNACE

Cozy High-Efficient Direct Vent Furnaces are a perfect heating solution for single-family residential, rental, vacation homes, apartment and below grade heating applications. They mount easily on any outside wall or, if walls for central placement within the living space. The sealed combustion chamber draws air for combustion from outside and exhausts through a concentric vent-pipe system to the outside - retaining heat and maintaining induced units include a standard vent kit that can be cut to fit wall thicknesses from 5"- 32" and includes an external vent cap which eliminates the need for expensive venting and unnecessary

labor. Enjoy 80+% AFUE efficiency by selecting a High-Efficient











## **HI-EFFICIENT DIRECT-VENT**

**WALL FURNACE** 



and other Man					
Model # -	HEDV253A	HEDV254A	HEDV403A	HEDV404A	
Type Gas	Nat.	L.P.	Nat.	L.P.	
BTU Input / Hr	25,000	25,000	40,000	40,000	
Dimensions (W x D x H)	24-1/2" x 9-3/4" * x 32-1/4"	24-1/2" x 9-3/4" * x 32-1/4"	34-5/8" x 9-3/4" * x 30-1/2"	34-5/8" x 9-3/4" * x 30-1/2"	
Weight	100 lbs	100 lbs	120 lbs	120 lbs	
Type Control	24 Volt	24 Volt	24 Volt	24 Volt	
Amps	1.88	1.88	2.18	2.18	
CFM	200	200	500	500	
Center Vent to Floor	12-1/2" adj.	12-1/2" adj.	12-1/2" adj.	12-1/2" adj.	
Gas Connection	3/8"	3/8"	3/8"	3/8"	

<sup>\*</sup>Dimensions do not include 5" Trim Kit. Total Depth = 14-3/4"

Tubular Aluminized Heat Exchanger enhances efficiencies and carries a 10 year warranty with no pro rata.





Standard Above Grade Vent Kit can be cut to fit 5" to 32" wall thickness. Diameter of wall opening is only 3-1/2".

Optional HEVK-5 Vent Exhaust Kit

Includes one 6' Black Flex Intake Pipe, one 5' Flocked Exhaust Tube, two 3" Couplings, three Support Brackets, three 2" Hose Clamps. (Note: 15' maximum with three vent exhaust kits).










Optional HEVE-5 Vent Enclosure Kit Includes one (1) 5' Enclosure body, (1) End Cap, (1) 24" Section Flexible Trim Strip.



Other Optional Accessories:

HEEL-1 90° ELBOW KIT - Contains one 90°, 2-inch aluminized, silicon wrapped steel elbow. (Note: May not use more than three on any unit installation - one comes with the unit).