

STUD SUPPORT BRACKET

» 533 SERIES

Stud Shoe

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____

SPECIFICATION

Sioux Chief 533 Series Stud Shoe stud support bracket, to be used to reinforce studs or joists that have been bored or notched to allow for piping. Install with a 1½" minimum length screw or nail in each of the bracket's provided holes. The Sioux Chief 533 Series Stud Shoe stud support bracket is NOT a total replacement of removed construction materials.

MATERIALS

16 gauge steel (.062" min)

DESIGN

Sioux Chief 533 series stud shoe stud support bracket is designed with a reinforcing rib that follows the contour of the pipe opening to provide maximum support and greater strength than similarly shaped stud support brackets. Sioux Chief 533 series can be used on both exterior or bearing walls and interior non-bearing walls when the installer adheres to the residential code requirements adopted in their municipality.

PIPE OPENING

Pipe opening (dimension D) is 2½" for use with any piping that is 2" Schedule 40 or smaller.

CAPACITY LOAD RATING


- 533-1: 552 lbs.
- 533-2: 810 lbs.
- 533-3: 945 lbs.

DIMENSIONS

A: width	
single stud	3.125"
double stud	4.7"
triple stud	3"
B: depth	3"
C: height	5.5"
D: pipe opening	2½"



533-1



Made in USA

Create Item Number

533- A

e.g. 533-2: Stud shoe support bracket for double studs

A	STUD NUMBER
<input type="checkbox"/> 1	Single studs
<input type="checkbox"/> 2	Double studs
<input type="checkbox"/> 3	Triple studs

