# **PITCHED ROOF FLASHINGS**



**NOTE: Aluminum** option material is recommended for oil and coal applications.


FLASHING -TGF or TGAF Fits roof pitch from 2/12 to 5/12.





SIZE	Α	
6"	22.25"	
7"	24.00"	
8"	24.00"	
10"	26.75"	
12"	29.00"	


FLASHING -TGF10 orTGAF10 Fits roof pitch from 6 /12 to 10/12.



SIZE	Α	В
6"	28.50"	23.50"
8"	30.75"	25.25"
*10"	35.35"	28.75"
*12"	37.50"	30.25"

Note: Available in galvanized only.


FLASHING -TGF15 orTGAF15 Fits roof pitch from 11/12 to 15/12.





SIZE	Α	В
6"	28.88"	21.00"
7"	30.50"	22.00"
8"	35.75"	28.50"
10"	38.40"	27.00"
12"	41.60"	29.00"

FLASHING -TGF24 orTGAF24 Fits roof pitch from 16/12 to 24/12.






SIZE	Α	В	
6"	38.00"	23.00"	
8"	43.50"	25.70"	

#### **FLAT ROOF FLASHINGS**




NOTE: In 6" - 8" aluminum option material is recommended for oil and coal applications.

FLAT TALL CONE FLASHING -6" - 8" TGFT OR TGAFT 10"-12" TGFT



FLAT TALL CONE FLASHING -14"-18" TGFT



5	
6"	22.25"
7"	24.00"
8"	24.00"
10"	26.75"
12"	29.00"
14"	33.00"
16"	35.00"
18"	37.00"

# **VERTICAL INSTALLATION KIT**

TGCK (Galvanized only) Available in 6", 7", & 8" Includes:

- Cap
- Flashing
- Storm Collar
- Painted Ceiling Support
- 48" Length MST Tape



#### **VERTICAL INSTALLATION KIT**

TGGCK5 (Galvanized) or TGCK5 (Stainless) Available in 6" & 8" Includes:

- Cap
- Flashing
- Storm Collar
- Painted Ceiling Support
- 36" Length of Pipe



### THROUGH THE WALL **INSTALLATION KIT**

TGGTWK (Galvanized) or TGTWK (Stainless) Available in 6" & 8"

- Includes:
- Cap
- Flashing • Storm Collar
- 2-Wall Bands
- Inuslated Tee Cap
- Wall Firestop
- Wall Support/Adapter
- 6" Length of Pipe
- Single Wall Adapter

