


**Tigerloop®**

**Bio™**

**NEW!**



**A standard Tigerloop® with B100 compatibility!**

Totally **Metallic** Housing



**Technical Information**

MAX. NOZZLE CAPACITY . . . . .	29.0 GPH
MAX. RETURN OIL FLOW . . . . .	31.7 GPH
TEMPERATURE RANGE . . . . .	20° - 105° F
MAX. INLET PRESSURE . . . . .	8 PSI
CONNECTIONS . . . . .	1/4" - NPT (female)
FUEL . . . . .	biofuels up to <b>B100</b> BioHeat®, No. 1 & 2 OIL


*Not for use with E-diesel or any fuel containing Ethanol (alcohol)*

Item No.	Description
S220-1	Tigerloop® Bio™ oil deaerator for biofuels to B100

**Tigerloop®**

**ULTRA-B™**

**NEW!**



**A standard Tigerloop® ULTRA™ with B100 compatibility!**

**Technical Information**


MAX. NOZZLE CAPACITY . . . . .	29.0 GPH
MAX. RETURN OIL FLOW . . . . .	31.7 GPH
TEMPERATURE RANGE. . . . .	20° - 105° F
MAX. INLET PRESSURE. . . . .	8 PSI
CONNECTIONS . . . . .	1/4" - NPT (female)
REPLACEMENT ELEMENT . . . . .	F100-10B
ELEMENT MEDIA . . . . .	15 Micron
ELEMENT CANISTER . . . . .	EPOXY INSIDE
FUEL . . . . .	biofuels up to <b>B100</b> BioHeat®, No. 1 & 2 HEATING OIL

*Not for use with E-diesel or any fuel containing Ethanol (alcohol)*

Item No.	Description
S220-9	Tigerloop® ULTRA™-B oil deaerator & filter



Totally **Metallic** Housing



**Tigerloop®**

**LT™**

**NEW!**

**A standard Tigerloop® for COLD CLIMATES!**

**Technical Information**

MAX. NOZZLE CAPACITY . . . . .	29.0 GPH
MAX. RETURN OIL FLOW . . . . .	31.7 GPH
TEMPERATURE RANGE. . . . .	-40° - 105° F
MAX. INLET PRESSURE. . . . .	8 PSI
CONNECTIONS . . . . .	1/4" - NPT (female)
FUEL . . . . .	biofuels up to <b>B5</b> BioHeat®, No. 1 & 2 HEATING OIL

*Not for use with E-diesel or any fuel containing Ethanol (alcohol)*

Item No.	Description
S220-17	Tigerloop® LT™ oil deaerator COLD CLIMATE



Totally **Metallic** Housing