



Features

- 15" apron.
- Tongue-and-groove walls with snap-together installation.
- High-gloss walls.
- Full caulking required in all seams.
- Acrylic towel bar.
- Aging In Place backerboards.

Material

- Made from solid Vikrell® material for strength, durability, and lasting beauty.

Installation

- Alcove.
- Right drain.

Recommended Products/Accessories

500C-59 Framed sliding bath door
690B-59 Framed sliding bath door
5405-59 Frameless sliding bath door
5900-57 Framed sliding bath door
5900-59 Framed sliding bath door
5905-57 Framed sliding bath door
5905-59 Framed sliding bath door
5906-59 Framed sliding bath door
5907-59 Framed sliding bath door
542808-59 Frameless sliding bath door
572005-59 Framed sliding shower door
581005-59 Frameless sliding bath door
80001012 12" straight grab bar
80001018 18" straight grab bar
80001024 24" straight grab bar
80011032 32" straight grab bar
80001036 36" straight grab bar
VA-80172 30" x 35" window trim kit
K-23726 Drain treatment
K-23733 Vikrell® cleaner

Included Components

Product consists of:
71044106 60" bath/shower wall set w/Aging in Place backerboards
71041120 60" bath



Codes/Standards



CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
HUD, UM Bulletin 73


Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell® Material

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	KOHLER Biscuit



Technical Information

All product dimensions are nominal.

Installation:	Three-wall alcove
Drain location:	Right
Basin area, bottom:	21" x 39" (533 mm x 991 mm)
Basin area, top:	24" x 53" (610 mm x 1346 mm)
Water depth:	10-1/4" (260 mm)
Water capacity:	35 gal (132.5 L)
Minimum flat for door:	1-3/4" (44 mm)
Maximum door height:	59-1/2" (1511 mm)
Maximum door width:	56-3/4" (1441 mm)

Notes

Install this product according to the installation instructions.

Studs should be positioned as shown.

Double studding is recommended for pivot shower door installations.

Attach grab bars at the specified backerboard locations only.