



# Location:



1-215-X  
Tub/Shower System  
**Specification Submittal**

Model Numbers	Feature Highlights
<input type="checkbox"/> <b>1-215-X</b> Tub and Shower System with Symmons Safetymix pressure balancing mixing valve	<ul style="list-style-type: none"> <li>• Symmons tub and shower system with a lever handle</li> <li>• Symmons Safetymix pressure balancing mixing valve with adjustable stop screw to limit handle turn</li> <li>• Integral service stops - allows water shut-off at valve for service</li> <li>• Diverter tub spout with twin ell and bushing adapter</li> <li>• Single mode, super showerhead #4-231 with arm and flange</li> <li>• Showerhead has adjustable flood or mist spray</li> <li>• Standard flow rate 2.0 gpm (7.6 L/min)</li> <li>• Polished chrome finish</li> </ul>
Options/ Modifications	
<input type="checkbox"/> <b>1.5</b> <b>1.5 gpm (5.7 L/min) flow restrictor</b> <input type="checkbox"/> <b>TRM</b> <b>Trim only, valve body ordered separately</b> <input type="checkbox"/> <b>X</b> <b>Integral stops - allows water shut off at valve for service. Recommended for use on all multiple commercial installations</b> <input type="checkbox"/> <b>X-CHKS</b> <b>Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve</b>	
<p><b>Note:</b> Append appropriate -suffix to model number.</p>	Warranty
Compliance	<p><b>Limited Lifetime</b> - to the original end purchaser in consumer/residential installations.  <b>10 Years</b> - for commercial/industrial installations. Refer to <a href="http://www.symmons.com/warranty">www.symmons.com/warranty</a> for complete warranty information.</p> 
<p>- ASME A112.18.1/CSA B125.1</p> 	

## Architectural/ Engineering Specification

Symmons Safetymix Tub and Shower System \_\_\_\_\_ Includes Symmons tub and shower system with a lever handle, Symmons Safetymix pressure balancing mixing valve with adjustable stop screw to limit handle turn, Integral service stops - allows water shut-off at valve for service, Diverter tub spout with twin ell and bushing adapter, Single mode, super showerhead #4-231 with arm and flange, Showerhead has adjustable flood or mist spray, Standard flow rate 2.0 gpm (7.6 L/min), Polished chrome finish 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1 compliant. Available options: "1.5 - 1.5 gpm (5.7 L/min) flow restrictor", "TRM - Trim only, valve body ordered separately", "X - Integral stops - allows water shut off at valve for service. Recommended for use on all multiple commercial installations", "X-CHKS - Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve".

1-215-X

## Dimensions

