# **KOHLER**

## One-piece compact elongated smart toilet, dual-flush K-5401-PA

### **Features**

- Compact, streamlined one-piece smart toilet with integrated personal cleansing
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- Tankless design with direct water supply
- Stainless steel wand offers adjustable spray shape, position, water pressure, temperature, pulsate, and oscillate functions
- Front and rear wash modes provide warm water for cleansing
- Self-cleaning function uses UV light and electrolyzed water systems to automatically clean the wand surfaces
- Warm-air drying system with adjustable temperature settings
- Automatic deodorization system
- Heated seat with adjustable temperature settings
- Motion-activated, hands-free opening/closing of cover
- Quiet-Close™ elongated lid and seat prevents slamming
- LED lighting illuminates the bowl to serve as a nightlight
- English-language touch-screen LCD remote control
- Emergency flush supports up to 100 flushes during power outage with simple touch-button activation
- Dual-flush technology allows you to choose between a full or partial flush
- Pump-assisted flushing for strong flush performance
- Dual flush offers a choice of 0.8 or 1.28 gpf (3.0 or 4.5 lpf)

### Installation

Standard 12" (305 mm) rough-in

### **Recommended Products/Accessories**

K-23726 Drain treatment





### Codes/Standards

ASME A112.19.2/CSA B45.1 ASME A112.4.2/CSA B45.16 ASME A112.19.14

AOME A112.15.14

DOE - Energy Policy Act 1992

EPA WaterSense®

California Energy Commission (CEC)

UL 1951

CSA C22.2 No. 14 CSA C22.2 No. 68

ADA

ICC/ANSI A117.1

**CSA B651** 

OBC

**IAPMO Certification** 

cUL Listed

# KOHLER® Intelligent Toilet and C3® Cleansing Seat Three-Year Limited Warranty

See website for detailed warranty information.

### **Available Colors/Finishes**

Color tiles intended for reference only.


Color Code Description

0 White

HB1 Honed Black



# One-piece compact elongated smart toilet, dual-flush K-5401-PA



## **Required Electrical Service**

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

120 V, 15 A, 60 Hz

### **Technical Information**

All product dimensions are nominal.

Toilet type: Floor-mount

Waste Outlet: Floor
Bowl shape: Elongated
Flush type: Class Five

Trap passageway: 1-15/16" (49 mm)

Water surface size: 7-15/16" x 5-5/8" (202 mm x 143 mm)

Rough-in: 12" (305 mm)

Fixture Supply Requirements

Min flow rate: 6 gpm (22.7 lpm)

#### Notes

Install this product according to the installation instructions.

This product is designed for installation with the electrical and water supplies located through either the wall or the floor.

IMPORTANT! Use the supply hoses provided with the fixture. Do not reuse the previously installed hoses.

Installation of a water hammer arrestor is recommended.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

