



A CSW Industrials Company

# PRODUCT DATA SHEET

## FOAM-A-COIL™

Coil Cleaner for Condensers & Evaporators

### Description

Non-acid, non-fuming FOAM-A-COIL™ removes grime, oil, grease and dust from air conditioning, air handling and all mechanical equipment, electronic and permanent air filters. A powerful, emulsifying surface-active foam actually lifts grease and dirt off of normally inaccessible surfaces. Cleaning with FOAM-A-COIL™ reduces the head pressure on overheated compressors, avoids premature equipment breakdown, increases equipment efficiency and decreases power consumption and costs. It is safe for all metals, aluminum and copper included, when directions are followed.

### Instructions

Read SDS, all directions, hazard and precautionary statements before using this product.

#### DIRECTIONS FOR USE: Mix well before use.

Appropriately dilute with water as needed and detailed below.

**For extremely dirty coils/equipment** - Dilute with 3 or 4 parts of water.

**For a continuous maintenance program** - Dilute with 6 to 10 parts water.

1. Apply the diluted solution with a trigger sprayer, hand powered tank or high pressure washer. To create a heavy foam, adjust nozzle for widest spray pattern and apply 1 or 2 inches away from coil or other surface. For a minimum foam adjust nozzle to narrowest spray pattern and apply from 6 to 8 inches away. Use a brush to help faster penetration of hard encrusted dirt. 2. Allow 5 to 10 minutes soaking time before rinsing.

Special Notes: On waxed and painted surfaces, FOAM-A-COIL should be rinsed off within a minute of application to avoid the possibility of removing the wax or fading the paint.

### Applications

Foam-A-Coil can be safely used on aluminum, copper, stainless steel or washable painted surfaces. It is formulated to clean metal coils, fibers and metal mesh filters, and other metal surfaces where acids cannot be used.

### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
82632	Gallon (3.8 L)	4 Bottles	45	1.21
82638	55 Gallons (208 L)	1 Drum	612	9.01



### Characteristics | Features

- Foaming action penetrates stubborn grease, tars and dirt. It disperses them so they can be rinsed away with water.
- Biodegradable
- Non-acid based, can be use indoors and outdoors
- Will not harm copper or aluminum
- Concentrated - dilute with water for economical use.
- Max foam

# FOAM-A-COIL™

## Coil Cleaner for Condensers & Evaporators

### Specifications

Wt/Gal @ 77°F	10.0 lbs./gal.
Flash Point SETA CC	None
Color	Bright Yellow/Green
Shelf Life	2 years



Nonfood Compounds  
P1

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



### **WARNING! CAUSES SERIOUS EYE IRRITATION**

#### **CONTAINS: Glycol Ether 34590-94-8 and Surfactant**

**127087-87-0. Precautionary Statements: PREVENTION:** Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. **RESPONSE - IF IN EYES:** Hold eyes open and rinse gently with water for 15 minutes. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. **IF SWALLOWED:** Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. **STORAGE:** Store in a well-ventilated place. Keep cool.

**DISPOSAL:** Dispose of contents/ container to an approved waste disposal plant.

**KEEP OUT OF REACH OF CHILDREN.**

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300. For additional information,  
refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345

### **Limited Warranty**

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50073-0420