

Slab Sensor, 10k

Submittal information
Revision D: Aug. 28, 2017

Project information

Job name:

Location:

Part no. ordered:

Engineer:

Date submitted:

Contractor:

Submitted by:

Manufacturer's representative:

Approved by:

Technical data

Ambient conditions:	32°F to 105°F (0°C to 41°C) 10% to 90% humidity (non-condensing)
Sensor type:	10k J-curve
Tolerance:	+/- 1% at 77°F (25°C)
Wire type:	22 gauge
Insulation:	Vulcanized sealed to prevent water penetration up to 9.8 ft. (3m)



Product information and application use

Slab sensors read temperature conditions to provide feedback and information to temperature control devices.

✓	Description	Part number	Diameter (OD)	Length	Lead length	Weight
	Slab Sensor, 10k	A9010599	0.19"	0.78"	12'	0.30 lbs.

Installation

Fasten the terminal connectors on the back of the thermostat. For more information, refer to the manuals for the Uponor Heat-only Thermostat with Touchscreen (A3100101) and the Uponor Wireless Digital Thermostat (A3800167).

Standards

Class II wiring

Codes

N/A

Listings

N/A

Related applications

Radiant heating and cooling Systems
Snow and ice melting systems
Permafrost protection systems
Turf conditioning systems

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
T 800.321.4739
F 952.891.2008
uponorpro.com

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4 CANADA
T 888.994.7726
F 800.638.9517
uponorpro.com