

Features

- Vitreous china.
- Drop-in or under-mount.
- 13-1/4" (337 mm) diameter

Recommended Accessories

K-9018 P-Trap

Components

Additional included component/s: Adjustable Linkage, and 1193643 Basin Clamps.





Codes/Standards ASME A112.19.2/CSA B45.1 ADA

ICC/ANSI A117.1 CSA B651 OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color Code Description


0	White
96	Biscuit
47	Almond



Compass® Bathroom Sink K-2298




Compass® Bathroom Sink K-2298



Technical Information

All product dimensions are nominal.

Installation:	Drop-in, Under-mount
Bowl area	Diameter: 10-5/8" (270 mm)
	Water depth: 4-3/4" (121 mm)
Drain hole:	1-3/4" (44 mm)
Template:	116214-7, required, included



	А
Drop-in	4-3/8" (137 mm)
Under-mount (shown)	4-3/8" (137 mm)

Notes

Install this product according to the installation instructions.

Spout must be a minimum of 4-1/2" (114 mm) long for adequate clearance into bathroom sink.

Supplied basin clamp assembly for under-mount installation requires 1" (25 mm) minimum countertop thickness. Installer must supply hardware for thinner countertops.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

