

Electronic Faucets

Batttery operated electronic faucet with above deck mixer to adjust water temperature – Goose Neck Spout

Model No: DEMD-211LF

COMPLIES WITH:

- IAPMO certified
- Complies to ASME A112.18.1/CSA B125.1
- Lindicates ADA compliance to ICC/ANSI A117.1/ADA
- Verified compliant with .25% weighted average Pb content regulations
- (Contact Delta Representative for State and/or Local Approvals)





NOTES:

Supplied as COMPLETE PRODUCT ONLY

Verified compliant with .25% weighted average Pb content regulations

SPECIFICATION:


- Deck mount electronic lavatory faucet
- Sensor detects user's hand to activate water flow
- Six 1.5V batteries (included)
- Adjustable maximum run time and optional Remote Control below
- Above deck electronics
- Red light indicator blinks when battery is low
- 0.5 gpm (1.9 L/min) aerator
- DEMD-211 SERIES Electronic faucet with mixer to adjust temperature
- Chrome Finish

OPERATION:

- $_{\odot}$ Sensing Range: (Factory set to 8.0" \pm 1.5" (200 mm \pm 40 mm) Adjustable from 3.15" to 11.8" (80 mm to 300 mm)
- Maximum Run Time:
 90 seconds, adjustable with remote control

(Dimensional drawing on following page)





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced June 18, 2015.