

GENUINE



For use as oil burner pump suction and return lines (not for nozzle line)

FLEXIBLE OIL LINES



For swing-out doors and oil deaerators

Steel Braided Covering - 24" and 36" Long - 145 PSI - 200 °F
For No. 1 and 2 heating oil, BioHeat® B5 or B20

*** DIN ISO 6806 APPROVED**

FLEXIBLE OIL LINES, Standard

Item No.	Description	BioFuels Rating
S220-24	Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 24" long* orange & black	
S220-36	Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 36" long* orange & black	
S220-40	Replacement fitting for flexible oil line, 3/8" inv. flare x 1/4"-NPT (no color for p/n S220-40)	
S222-36	Flexible oil line, braided steel covering, 3/8" Flare (FxF), 36" long* orange & black	
S223-24	BioFuels Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 24" long yellow & red	
S223-36	BioFuels Flexible oil line, braided steel covering, 1/4"- NPT (MxM), 36" long yellow & red	



FLEXIBLE OIL LINES

SPECIAL FOR RIELLO

Color coded Red & Blue for easy identification

European thread connects to **RIELLO** pump adaptor

Easy installation & service with two piece swivel connector



FLEXIBLE OIL LINES, Special for RIELLO burners

Item No.	Description	BioFuels Rating
S221-24	Flexible oil line for Riello burner, braided steel outside covering, blue & red 1/4"- NPT (M) x 1/4"- BSPP (RIELLO pump adapter thread), 24" long	
S221-36	Flexible oil line for Riello burner, braided steel outside covering, blue & red 1/4"- NPT (M) x 1/4"- BSPP (RIELLO pump adapter thread), 36" long*	
S220-61	Tigerloop® Mounting Bracket	
S220-62	Tigerloop® Ultra™ Bracket	

Service Advisory: All flexible oil lines should be inspected annually for deterioration (i.e. stiffness, cracks, etc.) and replaced every 3 years