

MARS 780 Definite Purpose Contactors

MARS SERIES **614**



MARS 780 Definite Purpose Contactors

MARS 780 - 2 pole contactors are designed for demanding applications. The enclosed body design provides quiet operation and improved durability by reducing the intrusion of dust and dirt. Silver-cadmium oxide contacts provide increased contact life when switching inductive loads.

Features:

- Enclosed body and coil – standard cover
- Push to test button
- Quad quick connects
- Box lugs - large window arch design
- Screw terminals and or box lugs available on 30 amp
- Coils - class F insulation

2 Pole 30 - 40 Amps

MARS No.	Furnas No.	FLA	Locked Rotor Amps			Non Inductive Amps	Coil Volts	Termination
			240V	480V	600V			
61345	45EG20AJ, 45CG20AJ, 45DG20AJ	30	180	150	120	40	24	Screw Type
61346	45EG20AF, 45CG20AF, 45DG20AF						120	
61347	45EG20AG, 45CG20AG, 45DG20AG						208-240	
61348	45EG20AL, 45CG20AL, 45DG20AL						277	
61349	45EG20AH, 45CG20AH, 45DG20AH						480	
61745	45EG20AJL	30	180	150	120	40	24	Box Lug
61746	45EG20AFL						120	
61747	45EG20AGL						208-240	
61748	45EG20ALL						277	
61749	45EG20AHL						480	
61755	45GG20AJL, 45FG20AJ, 45GG20AJ	40	240	200	160	50	24	Box Lug
61756	45GG20AFL, 45FG20AF, 45GG20AF						120	
61757	45GG20AGL, 45FG20AG, 45GG20AG						208-240	
61758	45GG20ALL, 45FG20AL, 45GG20AL						277	
61759	45GG20AHL, 45FG20AH, 45GG20AH						480	