

## Product Features:

- Accuracy:  $\pm 2.5\%$  of Span ( Grade B ANSI B40.1 )
- 1/4"-18 NPT Brass Connection ( Lower Mount )
- Black Corrosion Resistant Paint Steel Case with Clear Plastic Window
- Dual Scale: psi / kPa
- Bourdon Tube Style
- Operating Temperature:  
Ambient:  $-4^{\circ}\text{F}$  to  $140^{\circ}\text{F}$  (  $-20^{\circ}\text{C}$  to  $60^{\circ}\text{C}$  )  
Media: max.  $158^{\circ}\text{F}$  (  $70^{\circ}\text{C}$  )

## Application:

- For use with air, gas or water applications and medium that will not clog the connection port or corrode the copper alloy.  
(Examples: hydraulic and pneumatic systems, pumps, compressors, water systems and regulator)
- Not Approved for Potable Water Applications



**4PRO30PSI2PG**



**4PRO100PSI2PG**



**4PRO160PSI2PG**



**4PRO300PSI212PG**

Part#	Description	Dia. Face (in)	psi	kPa
4PRO30PSI2PG	PRESSURE GAUGE	2 in	0-30#	0-200#
4PRO100PSI2PG	PRESSURE GAUGE	2 in	0-100#	0-700#
4PRO160PSI2PG	PRESSURE GAUGE	2 in	0-160#	0-1100#
4PRO300PSI212PG	PRESSURE GAUGE	2-1/2 in	0-300#	0-2000#