

Features

- Spray performance delivers a drenching "rain" experience.
- Angled nozzles provide a full coverage spray.
- Adjustable swivel ball joint allows for precise spray adjustment.
- MasterClean™ sprayface resists hard water buildup and is easy to clean.
- Complements the Awaken® line.
- 1.75 gpm (7.6 lpm) flow rate.

Material

- KOHLER finishes resist corrosion and tarnishing.

Installation

- Installs as a ceiling or wall mount application.
- 1/2" NPT connection.
- Shower arm and flange sold separately.



Codes/Standards

ASME A112.18.1/CSA B125.1
DOE - Energy Policy Act 1992
EPA WaterSense®
California Energy Commission (CEC)


KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|--|------|-------------------------|
|  | CP | Polished Chrome |
|  | BN | Vibrant® Brushed Nickel |
|  | 2BZ | Oil-Rubbed Bronze |
|  | BL | Matte Black |



Technical Information

All product dimensions are nominal.

Showerhead/Body Spray:

Rated maximum flow: 2 gal/min (7.6 l/min)

Pressure: 45 psi (3.1 bar)

Notes

Install this product according to the installation instructions.