

Product Features:

- Accuracy: $\pm 2.5\%$ of Span (Grade B ANSI B40.1)
- 1/4"-18 NPT Brass Connection (Lower Mount)
- Black Corrosion Resistant Paint Steel Case with Clear Plastic Window
- Dual Scale: psi / kPa
- Bourdon Tube Style
- Operating Temperature:
Ambient: -4°F to 140°F (-20°C to 60°C)
Media: max. 158°F (70°C)

Application:

- For use with air, gas or water applications and medium that will not clog the connection port or corrode the copper alloy.
(Examples: hydraulic and pneumatic systems, pumps, compressors, water systems and regulator)
- Not Approved for Potable Water Applications



4PRO30PSI2PG



4PRO100PSI2PG



4PRO160PSI2PG



4PRO300PSI212PG

Part#	Description	Dia. Face (in)	psi	kPa
4PRO30PSI2PG	PRESSURE GAUGE	2 in	0-30#	0-200#
4PRO100PSI2PG	PRESSURE GAUGE	2 in	0-100#	0-700#
4PRO160PSI2PG	PRESSURE GAUGE	2 in	0-160#	0-1100#
4PRO300PSI212PG	PRESSURE GAUGE	2-1/2 in	0-300#	0-2000#