



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

## White PTFE Thread Seal Tape

### Design Features:

- 100% Polytetrafluoroethylene
- 3.5 Mil Thick
- .4 Density
- Imported

### Operating Specifications:

**Temperature:** -450° to +550° F\*

**Elongation Pressure:** 10000 psi



**Use:** For all industrial applications including water, oil, chemical, medical and food processing where non-contamination standards are high. To be used on all types of threaded fittings for passage of water, potable and non-potable, most chemicals, oxygen, gas, hydraulic and high pressure lines. Avoid using on molten alkali, certain halogen products and fluorine at high temperatures and pressures.

\*When heated over 500° F the PTFE will thermally degrade and decompose producing toxic fumes.

W-R#	Description	Weight	Min	Box
1001002	1/2" x 260"	0.020 lbs.	1	100
1001004	1/2" x 520"	0.030 lbs.	1	100
1001006	3/4" x 260"	0.030 lbs.	1	100
1001008	3/4" x 520"	0.045 lbs.	1	100

\*\*Meets & Exceeds MIL Spec T-27730A