

For Residential and Commercial Applications

Job Name _____
 Job Location _____
 Engineer _____
 Approval _____

Contractor _____
 Approval _____
 Contractor's P.O. No. _____
 Representative _____

LEAD FREE*

Series LF3004 Dielectric Unions

Sizes: 1/2" – 2"

Series LF3004 Dielectric Unions feature female iron pipe thread to female iron pipe thread (zinc plated) connections. These unions are designed to be installed to prevent accelerated corrosion and deterioration in the piping system due to galvanic and stray current. The LF3004 features Lead Free* construction to comply with Lead Free* installation requirements.

Features

- Female iron pipe thread to female iron pipe thread (zinc plated) connections.
- Designed and manufactured to the highest quality standards
- Individually factory certified to withstand a minimum of 600 volts on a dry line with no flashover
- Rated to 180°F (82°C) at 250psi (17.2 bar)

Specifications

A dielectric union shall be installed where indicated on the plans. The union shall feature a female iron pipe thread to female iron pipe thread (zinc plated) connections. The union shall be a Watts Series LF3004.

Materials – Dimensions – Weights

SIZE	MATERIALS					DIMENSIONS				WEIGHT	
	TAIL PIECE †	ADAPTER †	NUT †	INSULATOR	GASKET	A		B		oz.	gm
in.						in.	mm	in.	mm		
1/2	Steel	Steel	Steel	Polysulfone	Buna-N	1 1/8	41	2 1/4	57	7.8	221
3/4	Steel	Steel	Steel	Polysulfone	Buna-N	1 7/8	48	2 1/4	57	10.9	309
1	Steel	Steel	Steel	Polysulfone	Buna-N	2 1/4	58	2 1/2	64	16.6	471
1 1/4	Steel	Steel	Malleable Iron	Polysulfone	Buna-N	2 3/4	70	2 3/4	70	23.5	666
1 1/2	Malleable Iron	Malleable Iron	Malleable Iron	Polysulfone	Buna-N	3 1/2	89	2 3/4	70	44.5	1262
2	Malleable Iron	Malleable Iron	Malleable Iron	Polysulfone	Buna-N	4 1/8	105	3 1/8	79	67.2	1905

† Steel and malleable iron components are zinc plated

LF3004




Standards

Meets federal specifications for tensile strength and thread end connections

Pressure – Temperature

Maximum Pressure: 250psi (17.2 bar)

Maximum Temperature: 180°F (82°C)



NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

NOTICE

Inquire with governing authorities for local installation requirements

***The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.**

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com
Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca
Latin America: T: (52) 81-1001-8600 • Watts.com