



RESIDENTIAL/COMMERCIAL Second Stage Regulators Type 988LP



**988LP-03
988LP-35**



**Back Mount
988LP-34**

Product description

The second stage regulator reduces the pressure (10-5 psi) coming from a first stage regulator directly to the inlet pressure (11" w.c.) of the user appliance. Therefore Type 988 LP regulators are designed for Type A installations, see page 6 of the present catalogue. They have to be used outdoors in correct mounting position with venthole turned downwards. In the standard version these regulators are delivered with vent-hole in line with the inlet fitting.

Technical Specifications

Body And Cover: Aluminium
Diaphragm: Reinforced
Supplying Pressure: 5-15 PSIG
Cover Screws: Stainless Steel
Inlet Fitting Screws: Stainless Steel
Gas Type: Propane
Setting Point: inlet Pressure 10 PSIG, 140,000 BTU, Outlet Pressure 11" w.c.
Provided Flows: Flow Based On 10 PSIG Inlet Pressure and 20% Drop (In accordance with UL 144)
Type 988LP - L 6.027 x W 4.33 x H 4.94" Weight: 40.75 oz

Type (Part No.)	Capacities in BTU/hr propane	Inlet connection, inches	Outlet connection, inches	Outlet pressure range, inches w.c.	Outlet pressure setting, inches w.c.
988LP - 03 (98.1.890.0003)	800,000	1/2" NPT	1/2" NPT	9 to 13	11
988LP - 34 (98.1.890.0034)	650,000		3/4" NPT 90°		
988LP - 35 (98.1.890.0035)	500,000		1/2" NPT		

INSTALLATION
INSTRUCTIONS

RV AND OUTDOOR
COOKING REGULATORS

AUTOGAS
EQUIPMENT

FILLING
HEADS

BULK STORAGE AND
TRUCK EQUIPMENT

DOT/ASME
CONTAINER VALVES

REGULATORS