Lab Faucets

BL-5710-01 **Single Sink Faucet**

- 1/2" NPT female inlet
- 3/8" NPSM rigid gooseneck
- 11" (279 mm) height from center of inlet to top of gooseneck
- 5-5/8" (143 mm) gooseneck spread
- 8-1/2" (210 mm) distance from wall to outlet
- Specify hot or cold water
- Serrated hose tip




BL-5710-03 Same as BL-5710-01 except with swivel gooseneck

BL-5710-07 Same as BL-5710-01 except with rigid vacuum breaker nozzle, 10-1/16" (256 mm) height from center of inlet to top of vacuum breaker

BL-5710-09 Same as BL-5710-01 except with swivel vacuum breaker nozzle

BL-5860-01TL Same as BL-5710-01 except interior tin-lined for distilled water, with four arm handle

BL-5725-08 Sink Mixing Faucet







Inset: BL-5725-01 Same as BL-5725-08 except with standard rigid gooseneck

BL-5725-02 Same as BL-5725-01 except with standard swivel gooseneck

BL-5725-09 Same as BL-5725-08 except with swivel vacuum breaker gooseneck

BL-5715-08 Ledge Mixing Faucet

- Rigid vacuum breaker nozzle
- 1/2" NPT female inlets on 8" (203 mm) centers
- 3/8" NPSM rigid gooseneck
- 11-15/16" (303 mm) height from deck to top of vacuum breaker
- 5-7/16" (138 mm) nozzle spread
- Serrated hose tip





BL-5715-01 Same as BL-5715-08 except with standard rigid gooseneck (inset, above)

BL-5715-02 Same as BL-5715-01 except with standard swivel gooseneck

BL-5715-09 Same as BL-5715-08 except with swivel vacuum breaker nozzle

BL-5707-01 Single Science Table Faucet

- Vandal resistant single science table faucet
- 1/2" NPSM shank
- 2" (51 mm) diameter on base
- Two brass balls lock into table top indents to prevent vandalizing (drilling template included)
- 13-3/16" (335 mm) height
- 6-1/2" (166 mm) spread nozzle
- 1/2" NPT heavy duty riser pipe
- Serrated hose tip
- Tailpiece and nut furnished for optional 1/4" NPT connection



BL-5707-04 Same as BL-5707-01 except handle is 180° to nozzle