SLOAN.

OPTIONS

Power Type

Battery

Body Type

Mid

Mounting

Deck

Power Supply

Battery (BAT)

Sensor Type

Infrared (IR)

Flow Rate

0.5 gpm (2 Lpm) (0.5GPM) 0.35 gpm (1 Lpm) (0.35GPM)

Spray Type

Aerated (AER) Multi-Laminar (MLM)

Finish

Polished Chrome (CP) Brushed Stainless (SF)

Control Access

Above Deck

Mixer

Mixer Not Included Integrated Side Mixer (ISM)

Special Features

IQ Click (IQ) 10s Timeout (10S)

Compliances & Certifications

ADA Compliant ASME A112.18.1 Compliant CEC Compliant GPC 0.25 or less NYC604.4 Proposition 65 TAS UPC Certified UPC Low Lead Compliant cUPC Certified



Image for a standard EAF-250 shown

DESCRIPTION

Optima® Battery-Powered Deck-Mounted Mid Body Faucet

FEATURES

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Automatic Self-adapting Sensor Technology
- Low Battery Indicator
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 volt Lithium CR-P2 Commercial Battery included
- Appropriate Mounting Hardware included
- 3 year limited warranty

DOWNLOADS

- EAF 200/225/250/275 Installation Instructions
- EAF 200/225/250/275 (SP) Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 250 Repair and Maintenance Guide
- Additional Downloads



NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.