



Kingston™

Toilet tank with cover locks, 1.28 gpf
K-25100-T

Features

- Ideal for commercial installations.
- 1.28 gpf (4.8 lpf).
- Durable metal left-hand Polished Chrome trip lever.
- Tank cover locks included.
- Combines with a K-25076 or K-25076-SS bowl to create a complete K-25077-T or K-25077-SST Kingston two-piece toilet.

Technology

- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl, and trapway to create a strong siphon during flushing.
- Class Five® flushing technology offers virtually plug-free performance and rinsing power for a clean bowl.
- Class Five® canister allows water to flow out of the tank from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3" flapper for leak-free performance.

Installation

- Three-bolt quick-connect installation.
- Supply line sold separately.

Recommended Products/Accessories

K-23726 Drain treatment

Included Components

Additional Components:

Tank Cover, Trip Lever, and Hardware kit



Codes/Standards

ASME A112.19.2/CSA B45.1

KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------

	0	White
---	---	-------



Kingston™
Toilet tank with cover locks, 1.28 gpf
K-25100-T

No image available.
This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Toilet type: Two-piece, Bowl-mount
Waste Outlet: Floor
Flush type: Gravity siphon jet
Water Consumption
Full: 1.28 gpf (4.8 lpf)

Notes

Install this product according to the installation instructions.