

HANCOR SUMP PUMP WELL SPECIFICATION

Scope

This specification describes the Hancor sump pump well for use in residential drainage applications.

Requirements

The sump pump well shall be available in both 14-gallon (53 liter) and 19-gallon (72 liter) sizes. Each well shall have three pre-formed inlet collars sized to fit 4-inch (100mm) corrugated polyethylene drainage lines. Each well shall have a molded side panel designed to accept the outside basement perimeter line at any elevation along the well wall. Both wells shall have a twist-locking lid.

Material Properties

Sump pump well material shall be high density polyethylene.

Installation

Installation shall be in accordance with Hancor installation instructions and those issued by regional, state, or local agencies.

	A	B	C	D	E	F	G	H	I	J
14-gallon in.	12"	8"	14 1/4"	4 3/4"	20 3/8"	18 1/8"	24"	20 7/8"	18 3/8"	20 1/2"
53 liters (mm)	305mm	203mm	362mm	121mm	518mm	460mm	610mm	530mm	467mm	521mm
19-gallon in.	12	13	14 1/4	4 3/4	20 3/8	24	31 3/4	20 7/8	18 3/8	20 1/2
72 liters (mm)	(305)	(330)	(362)	(121)	(518)	(610)	(806)	(530)	(467)	(521)

