

## QS-style compression manifold fitting assemblies

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material Brass

73 °F (23 °C) at 160 psi (11 bar) Temp/pressure ratings 180 °F (82 °C) at 100 psi (6.9 bar)

200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required?

## Product information and application use

The Uponor R20 Compression Fitting Assembly threads onto manifold loop outlets. This R20 QS (Quick Seal) compression fitting connects Wirsbo hePEX™ or Uponor AquaPEX® tubing to the manifold in radiant heating applications and is designed for 5 /16",  $\frac{3}{8}$ ",  $\frac{1}{2}$ " or  $\frac{5}{8}$ " tubing. The R25 QS compression fitting does not directly thread onto the manifold, but onto other R25 connections, and is designed for use with  $\ensuremath{^{5}\!\!/_{8}}"$  and  $\ensuremath{^{3}\!\!/_{4}}"$  tubing only.





Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	Weight per UOM [lbs/UOM]	End Type 1	End Type 2
5/16" QS-style Compression Fitting Assembly, R20 thread	A4020313	1.372	1.187	1.057	-	0.26	QS 5/16"	ISO 228-G 3/4"
3/8" QS-style Compression Fitting Assembly, R20 thread	A4020375	1.372	1.187	1.004	0.95	0.23	QS 3/8"	ISO 228-G 3/4"
1/2" QS-style Compression Fitting Assembly, R20 thread	A4020500	1.372	1.187	1.004	0.95	0.21	QS 1/2"	ISO 228-G 3/4"
5/8" QS-style Compression Fitting Assembly, R20 thread	A4020625	1.372	1.187	1.004	0.95	0.19	QS 5/8"	ISO 228-G 3/4"
3/4" QS-style Compression Fitting Assembly, R25 thread	A4020750	1.66	1.5	1.099	1.18	0.33	QS 3/4"	ISO 228-G 1"
Replacement O-ring for insert (R25)	A4021000	0.934	0.934	0.07	-	0	-	-
Replacement O-ring for insert (R20)	A4021116	0.621	0.621	0.07	-	0	-	-
5/8" QS-style Compression Fitting Assembly, R25 thread	A4030625	1.729	1.5	1.064	1.18	0.4	QS 5/8"	ISO 228-G 1"

## Related applications

The R20-threaded Compression Fitting connects to Uponor manifold loop outlets. The compression end enables direct connection to Wirsbo hePEX tubing. Use the R25-threaded Compression Fitting for other R25 connections. For more information, refer to the Radiant Floor Heating Installation Handbook.

Radiant Heating and Cooling Systems Permafrost Protection Systems

Turf Conditioning Systems

Codes	Standards	Listings
IMC IRC NBC of Canada UMC	CSA B137.5 R32:	cNSFus-rfh ICC-ES-PMG 1012

Footnotes Contact information

Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008

Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517

<sup>\*</sup> Some SKUs in this family have additional codes, standards, or listings. Please see uponor.com for complete information.