υροποι

Ecoflex potable PEX plus coils

Project montation	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Ecoflex® Potable PEX Plus features Uponor AquaPEX® service pipe with a heat-trace cable running the length of the pipe to provide energy-efficient freeze protection. The pipe and heat-trace cable is protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use Ecoflex Potable PEX Plus for hot and cold potable-water applications.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part name		Part no.	Inner diameter coil [mm]	Outer diameter coil [mm]	Inner diameter pipe [mm]	Outer diameter pipe [mm]	Weight per UOM [kg/UOM]
1-1/4" Potable PEX Plus	with 5.5" Jacket, 5 W/ft. 240VAC	54555513	139.7	304.8	26.77	34.92	0.476
Part name	Part no.	Codes		Standards		Listings	
Ecoflex potable PEX plus coils	54555513	UPC IPC NI Canada UM	PC of IC NSPC IMC		STM F1960 CSA F876 NSF-61 NSF- 23	-	
In addition, the following parts have additional codes, standards, or listings:							
1-1/4" Potable PEX Plus with 5.5" Jacket, 5 W/ft. 240VAC	54555513						

Installation

Install Ecoflex Potable PEX Plus in hot or cold potable-water applications. Join pipes using Uponor ProPEX® or WIPEX™ fittings.2 Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For additional information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

Pre-Insulated Pipe Systems

Permafrost Prevention Systems

PEX-a Plumbing Systems

Footnotes	Contact information		
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	