

TSR3000

BSR1000

TRC

TS-48

WG-6

CT100

WG-100

# Campbell

## Installation Accessories



part	drop pipe	casing i.d.	pcs/pkg	SELF-CLAMPING WIRE & PIPE PROTECTOR
WG-100	1	4 to 6	48	
WG-125	1-1/4	4 to 6	48	

Slips around pipe when needed, squeezes together with a pair of pliers and stays put ... without tape or hose clamps. Won't slip, slide, float, or tilt.

- Molded, one-piece construction of virgin thermoplastic resin.
- Two large, snap-in holes to isolate wire and safety rope.
- Smooth edges to avoid damage to electrical cable.
- Open areas in design prevent "piston action" when pulling pump.
- Ready for use in 6" well casings (adaptable to 4" and 5" installations by cutting off tabs.)
- Fits standard galvanized pipe and 125-200 lb. poly pipe.



U.S. PAT. NO. 6,595,284  
CAN. PAT. NO. 1,205,738

part	drop pipe	casing i.d.	pcs/pkg	SNAP-IN CABLE GUARD
WG-6	1 or 1-1/4	4 to 6	100	

Molded polyethylene cable guards protect submersible wire from abrading against sides of well. Easy snap-in feature eliminates need for "fishing" wires through holes.



part	size	length	pcs/pkg	master ctn	CABLE TIE
CT100	1 to 1-1/4	8	100	—	
CT200	1-1/2 to 4	15-1/2	100	—	

Natural color nylon.

NOTE: Must be ordered in package quantities..

part	drop pipe	casing i.d.	pcs/pkg	TORQUE STOP (flexible pvc)
TS-48	1 to 2	4 to 8	12	

Installed directly above submersible pump to protect pump from starting torque damage. Injection molded from FDA-approvable PVC. Includes 2 stainless steel clamps.



part	drop pipe	casing i.d.	pcs/pkg	TORQUE RESISTOR (buna-n rubber)
TRC	1 to 2	4 to 8	28	


Installed directly above submersible pump to protect pump from starting torque damage. Includes 2 stainless steel clamps.



part	diameter	type	length	tensile strength
BSR500	1/4 in.	braided	500 ft.	1000 lb.
BSR1000	1/4 in.	braided	1000 ft.	1000 lb.
BSR3000	1/4 in.	braided	3000 ft.	1000 lb.
TSR500	1/4 in.	twisted	500 ft.	1000 lb.
TSR1000	1/4 in.	twisted	1000 ft.	1000 lb.
TSR3000	1/4 in.	twisted	3000 ft.	1000 lb.
ESR500	7/32 in.	braided	500 ft.	700 lb.
ESR1000	7/32 in.	braided	1000 ft.	700 lb.

Individually cartoned.

SAFETY ROPE  
(polypropylene)



Campbell Manufacturing, LLC  
127 East Spring Street, P.O. Box 207  
Bechtelsville, PA 19505-9153  
800-523-0224, Fax 610-369-3580