

SUBMITTAL SHEET

JOB NAME _____ ITEM TAG _____

JOB LOCATION _____ PART NUMBER _____

CONTRACTOR _____ DATE _____

ENGINEER APPROVAL _____ DATE _____

NO LEAD CURB STOP

Model T-5500NL

Lead-free design is suitable for all no lead potable water installations, in full compliance of all lead-free plumbing laws.

90-degree operation with enclosed operating head stops.

Operating head has been drilled to accept stationary rod cotter pin attachment.

Full-port, ball-and-seat design is superior to plug-type designs.

Durable, *Teflon-coated ball assures positive, bubble-tight shutoff, low torque operation and long service life.

For underground water service installations only.

- Third-party tested and certified in compliance with U.S. Federal Public Law 111-380
- NSF / ANSI 372 certified
- Manufactured in compliance to ANSI / AWWA C800-12 Specifications
- Female pipe thread connections comply with ANSI / ASME B1.20.1



Pictured Model T-5500NL

Working Pressure, Non Shock (PSI)

Cold working pressure (CWP): 300
Saturated steam (WSP): Not suitable for steam service



MATERIAL SPECIFICATION		
PART	MATERIAL	SPECIFICATION
1 Body	Lead-free cast bronze	ASTM B584 - UNS C89836
2 Seats (2)	BUNA-N (NBR) nitrilic rubber	Commercial grade
3 Operating head and stem (one piece)	Lead-free cast bronze	ASTM B584 - UNS C89836
4 Stem O-rings (2)	BUNA-N (NBR) nitrilic rubber	Commercial grade
5 Stem locknut	Lead-free cast bronze	ASTM B584 - UNS C89836
6 Ball	*Teflon coated lead-free cast bronze	ASTM B584 - UNS C89836
7 End Adapter	Lead-free cast bronze	ASTM B584 - UNS C89836

*Teflon and Nylon are a registered trademarks of the Dupont Company

DIMENSIONS				
Size	A	B	C	D
3/4"	1.59	2.82	2.54	.71
1"	1.60	3.41	2.78	.93
1-1/4"	1.60	4.72	2.78	.99
1-1/2"	2.02	4.64	3.45	1.37
2"	2.02	5.00	3.83	1.80

Pictured Model T-5500NL Cut-away

