

ProPEX lead-free (LF) copper tub ells

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material Copper Temp/pressure ratings 73 °F (2


73 °F (23 °C) at 160 psi (11 bar)

180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

Product information and application use

The ProPEX® Copper Tub EII, $\frac{1}{2}$ " PEX Lead-free (LF) Brass x $\frac{1}{2}$ " Copper is available for use in hot and cold domestic potable water systems. The copper tub ell is comprised of $\frac{1}{2}$ " copper pipe with an Uponor ProPEX Fitting on one end and the other end open



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	G [inch]	Weight per UOM [lbs/UOM]	End Type 1
ProPEX LF Copper Stub EII, 1/2" PEX LF Brass x 1/2" Copper (13" x 8")	LF2855050	7.987	0.709	12.299	3.084	8.372	0.77	13.32	0.5	ProPEX 1/2"
ProPEX LF Copper Stub EII, 1/2" PEX LF Brass x 1/2" Copper (3 1/2" x 8")	LF2865050	7.987	0.709	3.749	3.084	8.372	0.77	4.77	0.2	ProPEX 1/2"
ProPEX LF Copper Tub Ell, 1/2" PEX LF Brass x 1/2" Copper (3" x 6")	LF2875050	2.989	0.709	5.279	1.542	3.374	0.77	6.3	0.23	ProPEX 1/2"
ProPEX LF Copper Tub Ell, 1/2" PEX LF Brass x 1/2" Copper (3" x 4")	LF2885050	2.989	0.709	3.279	1.542	3.374	0.77	4.3	0.2	ProPEX 1/2"
ProPEX LF Copper Stub EII, 1" PEX x 1" Copper (13" x 8")	LF2891010	13	1.181	6.507	8	13.68	1.36	8.25	1.7	ProPEX 1"
ProPEX LF Copper Stub EII, 1/2" PEX LF Brass x 1/2" Copper (8" x 13")	LF2895050	12.985	0.709	7.295	3.04	13.37	0.77	8.316	0.48	ProPEX 1/2"
ProPEX LF Copper Stub EII, 3/4" PEX LF Brass x 3/4" Copper (4" x 8")	LF2897575	8.002	0.945	4.057	3.959	8.552	1.1	5.44	0.5	ProPEX 3/4"

Installation Related applications

Use compression fitting with a male national pipe thread (MNPT) adapter. Refer to the AquaPEX® Professional Plumbing Installation Guide for additional information.

PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Codes	Standards	Listings
UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	ASTM F877 ASTM F1960 CSA B137.5 NSF-61 NSF-14*	HUD MR 1269*

Footnotes	Contact information			
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
* Some SKUs in this family have additional codes, standards, or listings. Please see uponor.com for	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
complete information.	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		