



DropSpot™ Bottle Filler

DRS120-FIL-REF-BLK

Product description

Filtered, Refrigerated, Black, DropSpot™ On-wall Bottle Filler with Bi-level Cooler.

Compliances & Certifications



(ASME A112.18.1 Compliant, Michigan Filter First, IAPMO listed ASME, IGC 115, IGC 226, Meets Canada OBC and QBC, Filter listed to (NSF-42, NSF-53, NSF-401), NSF-61/CAN-61, NSF-372 Lead Free, Proposition 65, TAS, UL 399/CSA C22.2 No.120)

Code 33820030

Finish

 Black (BLK)

Downloads

- [↗ DRS120 Bottle Filler with Bi-Level Cooler Installation Instructions.pdf](#)
- [↗ FA3000-DRS110-120 Drop Down Filter Assembly Installation Instructions.pdf](#)
- [↗ FC3000 Replacement Water Filter Cartridge Installation Instructions.pdf](#)
- [↗ DropSpot™ Care and Cleaning Guide.pdf](#)
- [↗ Sloan DropSpot™ Bottle Fillers Brochure.pdf](#)
- [↗ Additional Downloads](#)

Videos

- [▶ Sloan DropSpot™ Bottle Fillers and Water Coolers](#)
- [▶ Sloan – Company Overview](#)
- [▶ Sloan DropSpot™ Bottle Fillers and Water Coolers Now at Wrigley Field](#)

Details

- Mounting: On-wall
- Configuration: Bottle Filler with Bi-level Cooler
- Filter Option: Filtered (REF)
- Refrigeration Option: Refrigerated (FIL)
- Finish: Black (BLK)
- Chilling Capacity: 8.0 gph (30.3 lph)
- Full Load Amps: 5.3
- Length: 19 (483mm)
- Width: 38 (965mm)
- Height: 39.6 (1006mm)
- Weight: 113lbs (51kg)
- Installation Location: Indoor
- Stations Served: 2
- Bottle Filler Water Flow Rate: Up to 1.2 gpm (4.5 Lpm)
- Bubbler Flow Rate: 0.3 gpm (1.1 Lpm)

Features

- Touch-free sensor operated bottle filler with 20 second max run time, Up to 1.2 gpm fill rate for quick fill with laminar flow
- Versatile mounting style allows for left-high or right-high installation, ADA compliant when installed properly
- Backlit LED light that illuminates bottle filling area when sensor is activated, Soft ambient white light to indicate filter status
- Bottle Counter Display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking
- Rough-in matches other manufacturers' recommended rough-in locations for easy replacement
- Antimicrobial bubbler, push bar, and other components
- Drop-down door assembly provides easy access to filter
- Patent pending push bar activates at any touch point and provides easy access for cartridge replacement
- Optional cane apron available for bi-level units to assist with ADA compliance (part 33830030, 33830031). Sold separately
- All models compatible with SC Argus Pro

Recommended specifications

Sloan's DropSpot™ On-wall Bottle Filler with Bi-level Cooler Filtered Refrigerated black powder coat. Chilling capacity of 8.0 gph of 50F drinking water, based on 80F inlet water and 90F ambient. Unit shall be activated from an antimicrobial front pushbar using less than 5 pounds of force. Bubbler shall deliver a 0.3 gpm flow. Basin and cabinet shall be constructed from galvanized steel with black powder coat finish. Bottle filler shall include sensor operated activation with a 20 second maximum run time. Bottle counter display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking. White light indicates the water filter status. Unit shall include LED lights that illuminate the bottle filling area. Bottle filler housing construction shall be black galvanized steel. Bottle filler shall provide up to 1.2 gpm flow rate with a laminar flow. Push bar shall be activated by any touch point on the bar and shall be opened by Sloan access key. Filter drop-down assembly shall be opened by Sloan access key. Filter used in the unit shall have capacity of 3000 gallons at a minimum, and shall reduce PFAS (PFOA and PFOS), lead, microplastic, cyst, chlorine and class 1 particles.

Power

- (Standard) 115VAC
- 60Hz
- 5.3A
- Provide Duplex Receptacle on GFCI Protected Circuit

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

