

Kingston™ Toilet tank, 1.28 gpf K-25100-RA

#### **Features**

- Ideal for commercial installations.
- 1.28 gpf (4.8 lpf).
- Durable metal right-hand Polished Chrome trip lever.
- Combines with a K-25076 or K-25076-SS bowl to create a complete K-25077-RA or K-25077-SSRA Kingston two-piece toilet.

# Technology

- Single-flush gravity uses the force of gravity and a precisionengineered tank, bowl, and trapway to create a strong siphon during flushing.
- Class Five® flushing technology offers virtually plug-free performance and rinsing power for a clean bowl.
- Class Five® canister allows water to flow out of the tank from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3" flapper for leak-free performance.

#### Installation

- Three-bolt quick-connect installation.
- Supply line sold separately.

## **Recommended Products/Accessories**

K-23726 Drain treatment

# **Included Components**

Additional Components:

Tank Cover, Trip Lever, and Hardware kit



# Codes/Standards

ASME A112.19.2/CSA B45.1

# KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0 White







No image available.

This product is a component and not intended to be a standalone installation.

## **Technical Information**

All product dimensions are nominal.

Toilet type: Two-piece, Bowl-mount

Waste Outlet: Floor

Flush type: Gravity siphon jet

Water Consumption

Full: 1.28 gpf (4.8 lpf)

## **Notes**

Install this product according to the installation instructions

Install this product according to the installation instructions.

