

"Apollo" Valves

SUBMITTAL SHEET

59 Series

Bronze Wye Strainer
APOLLOXPRESS®



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	



DESCRIPTION

The APOLLOXPRESS® Model YB-PR (59 Series) Strainers with quick Press connections are designed to protect domestic water systems and process equipment from unwanted foreign particles with minimal pressure loss. The valves are built for long reliable service with proven ASTM grade materials and stainless steel strainer. Features Leak Before Press® technology and 250 psig maximum working pressure.

FEATURES

- Fast, Reliable, Economical Press Installation
- Ridgid® XL Press Tool Compatible
- Leak Before Press® Technology
- Self-Aligning Screen Design
- Blowout Ball Valve Option
- CRN 0E8959.5C
- **Made in USA, ARRA Compliant**

PERFORMANCE RATING†

- Maximum Pressure:
250 psi (17.2 bar) non-shock
- Temperature Range:
0°F - 250°F (-18°C - 121°C)

†APOLLOXPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

OPTIONS

- (01) – 50 Mesh (Standard 1/2" models)
- (01) – 20 Mesh (Standard 3/4" - 2" models)
- (02) – Tapped Cap
- (P2) – Tapped Cap with Plug
- (06) – Tapped cap with Ball Valve
- (E1) – 20 Mesh (for 1/2" model)
- (A1) – 40 Mesh
- (B1) – 60 Mesh
- (C1) – 80 Mesh
- (H1) – 100 Mesh
- (59-PR-LF) Lead Free APOLLOXPRESS®

Not intended for potable water

STANDARD MATERIALS LIST

Part Name	Material
Body	Cast Bronze, ASTM B584
Cap	Brass, ASTM B16
Connector Housing	ASTM B16 Brass
Connector O-Ring	NSF grade EPDM
Screen	302 Stainless Steel
O-Ring	Teflon®
Gasket	PTFE

DIMENSIONS

Model Number	Part Number	Size (in.)	Length	Cv	Wt. (lbs.)
YB-12PR	59-003-01PR	1/2"	4.75"	5	1.0
YB-34PR	59-004-01PR	3/4"	6.1"	15	2.0
YB-1PR	59-005-01PR	1"	7.25"	28	3.0
YB-114PR	59-006-01PR	1-1/4"	7.62"	55	3.8
YB-112PR	59-007-01PR	1-1/2"	8.25"	70	5.7
YB-2PR	59-008-01PR	2"	10.39"	99	7.7

For liquids the flow coefficient - Cv - expresses the flow capacity in gallons per minute (GPM) of 60°F water with a pressure drop of 1 psi (lb/in²).

Apollo Valves, Manufactured by **Conbraco Industries, Inc.**
701 Matthews Mint-Hill Road, Matthews, NC 28105 USA
www.apollovalves.com | (704) 841-6000

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit our website @ www.apollovalves.com for the most current information.

