BECKETTLINK® CONNECTED TANK GAUGE SYSTEM

The BeckettLink® Connected Tank Gauge system is an electronic gauge that accurately and reliably measures the fuel level in your tank and transmits that information through a cloud-based connection to a smart phone or tablet. The information can also be sent to a fuel dealer's web-based 'Dealer Dashboard' monitoring system.

The system will also provide alerts to notify a user when the tank level is getting low so a delivery can be scheduled. This will reduce, if not eliminate, running out of fuel.

The system uses a paired gauge and hub to connect to a WiFi router. This provides a reliable connection to the internet and allows additional gauges and other connected devices to be added to the system as they become available.

Features and Benefits

- Gauge with Bluetooth® connection to hub
- Tank level can be accessed from a mobile device anywhere
- Hub that connects gauge to WiFi signal
- Easy set-up and connection through the BeckettLink® app
- · 150 ft. gauge to hub range
- · Works on tanks up to 72" dia.
- Standard Lithium battery in gauge with up to 10 year battery life
- · More accurate and reliable than a float gauge
- Information can be 'shared' with others using the BeckettLink® app

PeckettLink

- Multiple gauges can be connected to a single hub
- Tank adapter for 2"NPT and 'Euro' style tank fitting



OPERATION:

The BeckettLink tank gauge is mounted on an available opening on the top of the fuel storage tank. It senses fuel level every 4-1/2 hours and transmits the data via dedicated Bluetooth® signal to the BeckettLink hub. The hub converts the signal from the gauge to a data 'cloud' through an available WiFi connection. An app on the customers Smart Phone or Tablet can then be used to view fuel level, set alerts for when the fuel level is getting low, get alerts if the indoor temperature drops too low (if enabled), share information with others, and even find and connect to any BeckettLink participating dealer.

Description
BeckettLink®
Tank Gauge Kit - Complete

Complete Kit contains:

- 1) Ultrasonic tank gauge sensor
- 1) WiFi Connection Hub w/120VAC power adapter
- 1) Tank Adapter for 2" NPT or 'Euro' tank installation Ouick Start Guides and Hardware

Replacement Parts & Accessories		
Part #	Description	
7651A0001U	BeckettLink Tank Gauge - Only*	
7650A0001U	BeckettLink Hub	
7651GU	Gauge Replacement Gasket Kit**	
17022	2" MPT / Euro Tank Adapter	
17024	1-1/2" MPT Tank Adapter	
17026	1-1/4" MPT Tank Adapter	

Hub Specifications:

- · 4-1/16" Long
- · 4-1/16" Wide
- · 1-3/16" High

Power Supply

• 120VAC / 50-60Hz / 0.28A x 5VDC

Adapter (Included)

Hub to router = Signal strength displayed in app



Gauge Specifications:

Approved Fuels:

- · Fuel Oils
- · Kerosene
- Diesel fuel
- · Renewable Diesel Fuel
- · Biodiesel and biodiesel blends
- · Motor oils & gear oils

Dimensions:

Tank Gauge:

- · 4-1/2" High Overall
- · 3-5/8" High Installed
- · 3-18" Diameter

Power Supply - Gauge

- · 3VDC Lithium battery CR123A
- · Battery life Up to 10 years

Communications distance

• Gauge to Hub = 150ft

Tank Adapter:

- · 2" MPT w/ Flange to fit 'Euro' tanks
- · 1-7/8" High Overall
- · 5/8" High Flange to Top
- · 3-3/8" Diameter
- · 1-1/2"MPT & 1-1/4"MPT Adapters available (Sold Separately)

Note:

INTENDED FOR USE WITH COMBUSTIBLE PRODUCTS.NOT FOR USE WITH GASOLINE, LP GAS, OR ANY OTHER FLAMMABLE PRODUCTS. SEE INSTALLATION



Beckett BECKETTLINK® CONNECTED TANK GAUGE

The BeckettLink® Connected Tank Gauge system is an electronic gauge that accurately and reliably measures the fuel level in your tank and transmits that information through a cloud-based connection to a smart phone or tablet. The information can also be sent to a fuel dealer's web-based 'Dealer Dashboard' monitoring system.

The system will also provide alerts to notify a user when the tank level is getting low so a delivery can be scheduled. This will reduce, if not eliminate, running out of fuel.

The system uses a paired gauge and hub to connect to a WiFi router. This provides a reliable connection to the internet and allows additional gauges and other connected devices to be added to the system as they become available.

Features and Benefits

SYSTEM

- Gauge with Bluetooth® connection to hub
- Tank level can be accessed from a mobile device anywhere
- Hub that connects gauge to WiFi signal
- Easy set-up and connection through the BeckettLink® app
- · 150 ft. gauge to hub range
- · Works on tanks up to 72" dia.
- Standard Lithium battery in gauge with up to 10 year battery life
- More accurate and reliable than a float gauge
- Information can be 'shared' with others using the BeckettLink® app

PeckettLink

- Multiple gauges can be connected to a single hub
- Tank adapter for 2"NPT and 'Euro' style tank fitting





OPERATION:

The BeckettLink tank gauge is mounted on an available opening on the top of the fuel storage tank. It senses fuel level every 4-1/2 hours and transmits the data via dedicated Bluetooth® signal to the BeckettLink hub. The hub converts the signal from the gauge to a data 'cloud' through an available WiFi connection. An app on the customers Smart Phone or Tablet can then be used to view fuel level, set alerts for when the fuel level is getting low, get alerts if the indoor temperature drops too low (if enabled), share information with others, and even find and connect to any BeckettLink participating dealer.

Part #	Description
7651A0001K	BeckettLink® Tank Gauge Kit - Complete

Complete Kit contains:

- 1) Ultrasonic tank gauge sensor
- 1) WiFi Connection Hub w/ 120VAC power adapter
- 1) Tank Adapter for 2" NPT or 'Euro' tank installation Quick Start Guides and Hardware

Part #	Description
7651A0001U	BeckettLink Tank Gauge - Only*
7650A0001U	BeckettLink Hub
7651GU	Gauge Replacement Gasket Kit**
7022	2" MPT / Euro Tank Adapter
17024	1-1/2" MPT Tank Adapter
17026	1-1/4" MPT Tank Adapter

Hub Specifications:

- · 4-1/16" Long
- · 4-1/16" Wide
- · 1-3/16" High

Power Supply

- · 120VAC / 50-60Hz /
- 0.28A x 5VDC Adapter (Included)
- Hub to router = Signal strength displayed in app



Gauge Specifications:

Approved Fuels:

- · Fuel Oils
- · Kerosene
- · Diesel fuel
- · Renewable Diesel Fuel
- · Biodiesel and
- biodiesel blends
- · Motor oils & gear oils

Dimensions:

Tank Gauge:

- · 4-1/2" High Overall
- · 3-5/8" High Installed
- · 3-18" Diameter

Power Supply - Gauge

- · 3VDC Lithium battery CR123A
- · Battery life Up to 10 years

Communications distance

• Gauge to Hub = 150ft

Tank Adapter:

- · 2" MPT w/ Flange to fit 'Euro' tanks
- · 1-7/8" High Overall
- · 5/8" High Flange to Top
- · 3-3/8" Diameter
- · 1-1/2"MPT & 1-1/4"MPT Adapters available (Sold Separately)

Note:

INTENDED FOR USE WITH COMBUSTIBLE PRODUCTS NOT FOR USE WITH GASOLINE, LP GAS, OR ANY OTHER FLAMMABLE PRODUCTS. SEE INSTALLATION

