## KSDB-3322

## Swanstone Double Bowl Kitchen Sink





#### **Manufactured from Swanstone Solid Surface**

Recommended for high-use traffic areas and commercial surfaces.

#### **FEATURES**

- · Swan's most popular sink.
- Classic style in a standard size.
- · Renewable surface will not wear away.
- · Hot pots and boiling water will not damage it.
- · Highest resistance of impact from heavy objects.
- · Easily accommodates all faucet styles.
- Heat, stain and scratch resistant for lasting beauty.
- Warranty: Limited Lifetime Residential Limited 10-year - Commercial





Capacity: 7 1/4 gallons in large (left) bowl, 5 3/4 gallons in small (right) bowl

#### **SPECIFICATIONS**

Model	Part	Nominal Dimensions			Carton Dims. In.	Cu. Ft.
KSDB-3322	KS03322DB	33" W x 22" D	33	FedEx	26 x 13 x 39	7.63
	(	(838 mm x 559 m	m)			

## **COLORS**

## **Solid Colors:**

- White (010)
- Bisque (018)
- Bone (037)

### **Aggregate Colors:**

- Arctic Granite (035)
- Baby's Breath (168)
- Barley (091)
- Bermuda Sand (040)
- Canyon (124)
- Cloud Bone (126)
- Cloud White (125)
- Glacier (121)

- Golden Steppe (128)
- Gray Granite (042)
- Ice (130)
- Mountain Haze (129)
- Night Sky (012)
- Pebble (072)
- Prairie (122)

- Tahiti Desert (050)
- Tahiti Gray (053)
- Tahiti Ivory (059)
- Tahiti Matrix (058)
- Tahiti Sand (051)
- Tahiti White (011)
- Tundra (131)

## STANDARDS AND RATINGS

American National Standard Institute— ANSI Z124.6

International Association of Plumbing and Mechanical Officials (IAPMO)—Listed

cUPC listed—Certified to CSA Test Standard B45.5 by IAPMO

Uniform Plumbing Code (UPC)

National Sanitation Foundation-NSF/ANSI 51 Food Equipment Materials

For a complete list of tests and results see the Technical Data Sheet.

# MAINTENANCE AND CLEANING INFORMATION

Clean your Swanstone sink by using abrasive cleaners or other similar products. Use of a nylon scouring pad or Mr. Clean® Magic Eraser® is also recommended. Food-based stains can be removed using a 50-50 mix of bleach and water solution and soaking for 15 minutes. For rust or other mineral stains, rust-removing products are acceptable. **Do not** use metal scouring pads.

#### SUPPORT DOCUMENTS

Installation instructions available at **swanstone.com**.

