

### **OPTIONS**

### **Power Type**

Hardwired

### **Body Type**

Mid

### Mounting

Deck

# **Power Supply**

Hardwired Less Transformer (HLT) Plug Adapter (PLG)

# **Sensor Type**

Infrared

### Flow Rate

0.35 gpm (1.3 Lpm) (0.35GPM) 0.5 gpm (1.9 Lpm) (0.5GPM) 1.0 gpm (3.8 Lpm) (1.0GPM)

### **Spray Type**

Multi-Laminar (MLM)
Aerated (AER)
Laminar (LAM)

## Finish

Polished Chrome (CP) Polished Brass (PB) Brushed Stainless (SF) Brushed Nickel (BN) Graphite (GR)

# **Control Access**

Above Deck

## Mixer

Integrated Side Mixer (ISM)
Mixer Not Included
Integrated Thermostatic Mixer (ITM)

# **Special Features**

IQ Click (IQ)
Carbon Offset (CO)
IC Click (IC)
Drain Pop Up (DPU)

# **Compliances & Certifications**

ADA Compliant ASME A112.18.1 Compliant CEC Compliant



## **DESCRIPTION**

Optima® Hardwired-Powered Deck-Mounted Mid Body

### **FEATURES**

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Automatic Self-adapting Sensor Technology
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 Volt DC Plug-in Adapter (must be ordered separately for Less Adapter/Transformer (-LT) faucets)
- Appropriate Mounting Hardware included
- 3 year limited warranty

## **DOWNLOADS**

- EAF 200/225/250/275 Installation Instructions
- EAF 200/225/250/275 (SP) Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima Plus EAF 200 Repair and Maintenance Guide
- Trim Plate Guide
- Additional Downloads

## **VIDEOS**



Sloan Connect App®



EPD

HPD

NSF-61

NYC604.4

Proposition 65

TAS

**UPC** Certified

# **NOTES**

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.