

Uponor AquaPEX reclaimed water coils and straight lengths

Project Information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Product Information and application use

Uponor AquaPEX® reclaimed water tubing is used in reclaimed water (graywater) systems. The tubing is color-coded purple for easy distinction in the plumbing system. It distributes non-potable water for designated applications (laundry, toilet and residential irrigation).



Part name	Part no.	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Weight per UOM [lbs/UOM]
1/2" Uponor AquaPEX Purple Reclaimed Water, 300-ft. coil	F1060502	19.7	32	4	0.475	0.625	18
3/4" Uponor AquaPEX Purple Reclaimed Water, 300-ft. coil	F1060752	21	32	8	0.671	0.875	34
1" Uponor AquaPEX Purple Reclaimed Water, 300-ft. coil	F1061002	22.7	32	16	0.862	1.125	56
1 1/4" Uponor AquaPEX Purple Reclaimed Water, 10-ft. straight length, 50 ft. (5 per bundle)	F1911256	4	126	4	1.054	1.375	16
1 1/2" Uponor AquaPEX Purple Reclaimed Water, 10-ft. straight length, 50 ft. (5 per bundle)	F1911506	4	126	4	1.244	1.625	21
2" Uponor AquaPEX Purple Reclaimed Water, 10-ft. straight length, 50 ft. (5 per bundle)	F1912006	7	126	7	1.629	2.125	34
1" Uponor AquaPEX Purple Reclaimed Water, 20-ft. straight length, 200 ft. (10 per bundle)	F1921002	4	258	4	0.862	1.125	35
1" Uponor AquaPEX Purple Reclaimed Water, 10-ft. straight length, 100 ft. (10 per bundle)	F1961002	4	126	4	0.862	1.125	17.5
1 1/4" Uponor AquaPEX Purple Reclaimed Water, 20-ft. straight length, 100 ft. (5 per bundle)	F1961256	4	258	4	1.054	1.375	32.0001
1 1/2" Uponor AquaPEX Purple Reclaimed Water, 20-ft. straight length, 100 ft. (5 per bundle)	F1961502	5	258	5	1.244	1.625	42
2" Uponor AquaPEX Purple Reclaimed Water, 20-ft. straight length, 100 ft. (5 per bundle)	F1962002	8	258	8	1.629	2.125	68.1

Installation

ProPEX® fittings are approved for use with Uponor AquaPEX reclaimed water tubing. Refer to the Uponor professional plumbing installation guide for more information.

Related applications

PEX-a Plumbing Systems

Codes

IMC|UPC|IBC|IRC|NBC of Canada|IPC|IFGS|NPC of Canada|UMC|NSPC

Standards

ASTM F1960|ASTM E119|UL 263|ASTM F876|ASTM E84|ASTM F2023|ASTM E814|ULC S115|ASTM F877|CSA B128.1|CSA B137.5|ULC S102.2|ULC S101|NSF-14*

Listings

IAPMO-ES|ICC-ES-PMG|PPI TR-4|CSA|U.P.Code|cQAlus P321|HUD MR 1269|cNSFus-rw|BMEC

Footnotes

* Some SKUs in this family have additional codes, standards, or listings. Please see uponor.com for complete information.

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517