

in sink erator

Dimensions

11¹/₂"



Dishwasher Drain

-5

* Distance from bottom of sink to center line of disposer outlet. Add 1/2" when stainless steel sinks are used.
** Length of tailpipe from center line of disposer outlet

to end of tailpipe. NOTE: Plumb waste line to prevent

standing water in disposer motor housing.

Job Specifications

Connection

6"

STANDARD SERIES

Badger[®] 1

Submittal Sheet

This model offers the following features and benefits:

- Lift & Latch[®] technology for easier sink connection
- 1/3 Horsepower Heavy Duty Motor (Quiet Dura-Drive[®] Induction Motor)
- We Come To You[®] 1-Year In-Home Limited Warranty
- Rugged Galvanized Steel Construction (For Disposer Durability)
- Space-Saving Compact Design
- Available with or without a factory installed power cord.

Sample Specification

Food Waste Disposer(s) shall be InSinkErator Badger[®] 1, continuous feed, with 1/3 HP. motor, stainless steel grinding elements with two stainless steel 360° swivel lugs. Exclusive self-service wrench.

Warranty

1-Year *We Come to You*[®] Limited In Home Warranty

 The complete InSinkErator warranty is included in the Care & Use Booklet packed with each unit.

INVENTED, DESIGNED & ASSEMBLED in the USA

Specifications

Continuous Wall Switch Single Phase //3 20 50 725 5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 12 lbs. 10 oz. (without cord) 2 lbs. 10 oz. (with cord) 11/2″
Single Phase //3 20 50 725 5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 2 lbs. 10 oz. (without cord) 2 lbs. 14 oz. (with cord)
/3 20 50 725 5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 2 lbs. 10 oz. (without cord) 2 lbs. 14 oz. (with cord)
20 50 725 5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 2 lbs. 10 oz. (without cord) 2 lbs. 14 oz. (with cord)
50 725 5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord)
725 5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 2 Ibs. 10 oz. (without cord) 2 Ibs. 14 oz. (with cord)
5.6 ntermittent Permanently Lubricated Jpper & Lower Bearings 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord)
ntermittent Permanently Lubricated Jpper & Lower Bearings 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord)
Permanently Lubricated Jpper & Lower Bearings 12 lbs. 10 oz. (without cord) 2 lbs. 14 oz. (with cord)
Jpper & Lower Bearings 2 lbs. 10 oz. (without cord) 2 lbs. 14 oz. (with cord)
2 lbs. 14 oz. (with cord)
1-1/2″
26 oz.
Manual Reset Overload
Approx. 1 Gallon per Person Per Day
3-4 KWh per Year
-1/2" Cushioned Slip Joint
Yes
Available with or without



Food waste is roughly 80% water. By using your disposal regularly, you can help divert food waste from landfills and reduce greenhouse gas emissions. Make sustainability a family affair by using your disposal. After all, the smallest changes can make the biggest impact.



1-800-558-5700 www.insinkerator.com